

# SAFETY DATA SHEET

1-171 Uni Thinner Very Slow



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : 1-171 Uni Thinner Very Slow  
**Product type** : Liquid.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses            |
|----------------------------|
| Use in coatings - Thinner. |

### 1.3 Details of the supplier of the safety data sheet

Valspar b.v.  
Zuiveringweg 89  
8243 PE Lelystad  
The Netherlands

tel: +31 (0)320 292200  
fax: +31 (0)320 292201

valspar

**e-mail address of person responsible for this SDS** : msds@valspar.com

#### National contact

GPS Automotive Lelystad  
tel: +31 (0)320 292288  
fax: +31 (0)320 292201

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : UK: 0-800-014-8126  
CALL: +(44)-870-8200418 (Hours of operation - 24 hours)

Ireland: +353 1 8092566 Beaumont Hospital - National Poisons Information Centre  
CALL: +(353)-19014670 (Hours of operation - 24 hours)

#### Supplier

**Telephone number** : Call: +31 (0)320 292200 (during daytime)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Eye Irrit. 2, H319  
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : F; R11  
Xn; R20/21  
R66

**Physical/chemical hazards** : Highly flammable.

## SECTION 2: Hazards identification

**Human health hazards** : Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### Precautionary statements

**Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.

**Response** : IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

**Storage** : Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** : n-butyl acetate  
acetone

**Supplemental label elements** : Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

**SECTION 3: Composition/information on ingredients**

| Product/ingredient name | Identifiers  | w%        | Classification   |  | Type    |
|-------------------------|--|-----------|--|--|---------|
|                         |  |           | 67/548/EEC   | Regulation (EC) No. 1272/2008 [CLP]  |         |
| 2-butoxyethyl acetate   | REACH #:<br>01-2119475112-47<br>EC: 203-933-3<br>CAS: 112-07-2<br>Index: 607-038-00-2  | ≥10 - ≤25 | Xn; R20/21   | Acute Tox. 4, H312<br>Acute Tox. 3, H331   | [1] [2] |
| n-butyl acetate         | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1  | ≥10 - ≤25 | R10<br>R66, R67  | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066  | [1]     |
| xylene                  | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | <10       | R10<br>Xn; R20/21<br>Xi; R38   | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 | [1] [2] |
| acetone                 | REACH #:<br>01-2119471330-49<br>EC: 200-662-2<br>CAS: 67-64-1<br>Index: 606-001-00-8   | ≤10       | F; R11<br>Xi; R36<br>R66, R67  | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066  | [1] [2] |
| ethylbenzene            | REACH #:<br>01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4  | ≤2.2      | F; R11<br>Xn; R20, R48/20,<br>R65  | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373<br>(hearing organs)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3,<br>H412                                     | [1] [2] |
| toluene                 | REACH #:<br>01-2119471310-51<br>EC: 203-625-9<br>CAS: 108-88-3<br>Index: 601-021-00-3  | ≤0.3      | F; R11<br>Repr. Cat. 3; R63<br>Xn; R48/20, R65<br>Xi; R38<br>R67         | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Repr. 2, H361d<br>(Unborn child)<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304                               | [1] [2] |
|                         |  |           | <b>See Section 16 for the full text of the R-phrases declared above.</b> | <b>See Section 16 for the full text of the H statements declared above.</b>  |         |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

## SECTION 5: Firefighting measures

**Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

## SECTION 7: Handling and storage

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name | Exposure limit values   |
|-------------------------|---|
| 2-butoxyethyl acetate   | <b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b><br>STEL: 333 mg/m <sup>3</sup> 15 minutes.<br>STEL: 50 ppm 15 minutes.<br>TWA: 133 mg/m <sup>3</sup> 8 hours.<br>TWA: 20 ppm 8 hours.  |
| xylene                  | <b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b><br>STEL: 442 mg/m <sup>3</sup> , 0 times per shift, 15 minutes.<br>STEL: 100 ppm, 0 times per shift, 15 minutes.<br>TWA: 221 mg/m <sup>3</sup> , 0 times per shift, 8 hours.<br>TWA: 50 ppm, 0 times per shift, 8 hours. |
| acetone                 | <b>EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values</b><br>TWA: 500 ppm 8 hours.<br>TWA: 1210 mg/m <sup>3</sup> 8 hours.  |
| ethylbenzene            | <b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b><br>STEL: 884 mg/m <sup>3</sup> 15 minutes.<br>STEL: 200 ppm 15 minutes.<br>TWA: 442 mg/m <sup>3</sup> 8 hours.<br>TWA: 100 ppm 8 hours.  |
| toluene                 | <b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b><br>STEL: 384 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 192 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.   |

**SECTION 8: Exposure controls/personal protection**

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

| Product/ingredient name | Type | Exposure              | Value                    | Population | Effects  |
|-------------------------|------|-----------------------|--------------------------|------------|----------|
| 2-butoxyethyl acetate   | DNEL | Short term Inhalation | 333 mg/m <sup>3</sup>    | Workers    | Local    |
|                         | DNEL | Short term Inhalation | 775 mg/m <sup>3</sup>    | Workers    | Systemic |
|                         | DNEL | Short term Dermal     | 102 mg/kg bw/day         | Workers    | Systemic |
|                         | DNEL | Long term Inhalation  | 133 mg/m <sup>3</sup>    | Workers    | Systemic |
|                         | DNEL | Long term Dermal      | 102 mg/kg bw/day         | Workers    | Systemic |
|                         | DNEL | Short term Inhalation | 166 mg/m <sup>3</sup>    | Consumers  | Local    |
|                         | DNEL | Short term Inhalation | 499 mg/m <sup>3</sup>    | Consumers  | Systemic |
|                         | DNEL | Short term Dermal     | 27 mg/kg bw/day          | Consumers  | Systemic |
|                         | DNEL | Short term Oral       | 18 mg/kg bw/day          | Consumers  | Systemic |
|                         | DNEL | Long term Inhalation  | 67 mg/m <sup>3</sup>     | Consumers  | Systemic |
|                         | DNEL | Long term Dermal      | 36 mg/kg bw/day          | Consumers  | Systemic |
|                         | DNEL | Long term Oral        | 4.3 mg/kg bw/day         | Consumers  | Systemic |
| n-butyl acetate         | DNEL | Short term Inhalation | 480 mg/m <sup>3</sup>    | Workers    | Systemic |
|                         | DNEL | Short term Inhalation | 960 mg/m <sup>3</sup>    | Workers    | Local    |
|                         | DNEL | Long term Inhalation  | 480 mg/m <sup>3</sup>    | Workers    | Systemic |
|                         | DNEL | Long term Inhalation  | 480 mg/m <sup>3</sup>    | Workers    | Local    |
|                         | DNEL | Short term Inhalation | 859.7 mg/m <sup>3</sup>  | Consumers  | Systemic |
|                         | DNEL | Short term Inhalation | 859.7 mg/m <sup>3</sup>  | Consumers  | Local    |
|                         | DNEL | Long term Inhalation  | 102.34 mg/m <sup>3</sup> | Consumers  | Systemic |
|                         | DNEL | Long term Inhalation  | 102.34 mg/m <sup>3</sup> | Consumers  | Local    |
| xylene                  | DNEL | Short term Inhalation | 289 mg/m <sup>3</sup>    | Workers    | Local    |
|                         | DNEL | Short term Inhalation | 289 mg/m <sup>3</sup>    | Workers    | Systemic |
|                         | DNEL | Long term Inhalation  | 221 mg/m <sup>3</sup>    | Workers    | Systemic |
|                         | DNEL | Long term Dermal      | 180 mg/kg                | Workers    | Systemic |

### SECTION 8: Exposure controls/personal protection

|              |                |                       |                        |           |          |
|--------------|----------------|-----------------------|------------------------|-----------|----------|
| acetone      | DNEL           | Short term Inhalation | 174 mg/m <sup>3</sup>  | Consumers | Local    |
|              | DNEL           | Short term Inhalation | 174 mg/m <sup>3</sup>  | Consumers | Systemic |
|              | DNEL           | Long term Inhalation  | 14.8 mg/m <sup>3</sup> | Consumers | Systemic |
|              | DNEL           | Long term Dermal      | 108 mg/kg              | Consumers | Systemic |
|              | DNEL           | Long term Oral        | 1.6 mg/kg              | Consumers | Systemic |
|              | DNEL           | Long term Inhalation  | 1210 mg/m <sup>3</sup> | Workers   | Systemic |
|              | DNEL           | Short term Inhalation | 2420 mg/m <sup>3</sup> | Workers   | Local    |
|              | DNEL           | Long term Dermal      | 186 mg/kg bw/day       | Workers   | Systemic |
|              | DNEL           | Long term Oral        | 62 mg/kg bw/day        | Consumers | Systemic |
|              | DNEL           | Long term Dermal      | 62 mg/kg bw/day        | Consumers | Systemic |
| ethylbenzene | DNEL           | Long term Inhalation  | 200 mg/m <sup>3</sup>  | Consumers | Systemic |
|              | DNEL           | Long term Inhalation  | 77 mg/m <sup>3</sup>   | Workers   | Systemic |
|              | DNEL           | Long term Dermal      | 180 mg/kg bw/day       | Workers   | Systemic |
|              | DNEL           | Long term Inhalation  | 15 mg/m <sup>3</sup>   | Consumers | Systemic |
| toluene      | DNEL           | Long term Oral        | 1.6 mg/kg bw/day       | Consumers | Systemic |
|              | DNEL           | Short term Inhalation | 384 mg/m <sup>3</sup>  | Workers   | Local    |
|              | DNEL           | Short term Inhalation | 384 mg/m <sup>3</sup>  | Workers   | Systemic |
|              | DNEL           | Long term Inhalation  | 192 mg/m <sup>3</sup>  | Workers   | Local    |
|              | DNEL           | Long term Inhalation  | 192 mg/m <sup>3</sup>  | Workers   | Systemic |
|              | DNEL           | Long term Dermal      | 384 mg/kg bw/day       | Workers   | Systemic |
|              | DNEL           | Short term Inhalation | 226 mg/m <sup>3</sup>  | Consumers | Local    |
|              | DNEL           | Short term Inhalation | 226 mg/m <sup>3</sup>  | Consumers | Systemic |
|              | DNEL           | Long term Inhalation  | 56.5 mg/m <sup>3</sup> | Consumers | Systemic |
|              | DNEL           | Long term Dermal      | 226 mg/kg bw/day       | Consumers | Systemic |
| DNEL         | Long term Oral | 8.13 mg/kg bw/day     | Consumers              | Systemic  |          |

#### PNECs

| Product/ingredient name | Compartment Detail     | Value        | Method Detail |
|-------------------------|------------------------|--------------|---------------|
| 2-butoxyethyl acetate   | Fresh water            | 0.304 mg/l   | -             |
|                         | Marine                 | 0.0304 mg/l  | -             |
|                         | Fresh water sediment   | 2.03 mg/kg   | -             |
|                         | Marine water sediment  | 0.203 mg/kg  | -             |
|                         | Soil                   | 0.68 mg/kg   | -             |
|                         | Sewage Treatment Plant | 90 mg/l      | -             |
| n-butyl acetate         | Fresh water            | 0.18 mg/l    | -             |
|                         | Marine                 | 0.018 mg/l   | -             |
|                         | Fresh water sediment   | 0.981 mg/kg  | -             |
|                         | Marine water sediment  | 0.0981 mg/kg | -             |

## SECTION 8: Exposure controls/personal protection

|                        |                        |              |           |
|------------------------|------------------------|--------------|-----------|
| xylene                 | Soil                   | 0.0903 mg/kg | -         |
|                        | Sewage Treatment Plant | 35.6 mg/l    | -         |
|                        | Fresh water            | 0.327 mg/l   | -         |
|                        | Marine water           | 0.327 mg/l   | -         |
|                        | Fresh water sediment   | 12.46 mg/kg  | -         |
|                        | Marine water sediment  | 12.46 mg/kg  | -         |
|                        | Soil                   | 2.31 mg/kg   | -         |
|                        | Sewage Treatment Plant | 6.58 mg/l    | -         |
|                        | acetone                | Fresh water  | 10.6 mg/l |
| Marine                 |                        | 1.06 mg/l    | -         |
| Fresh water sediment   |                        | 30.4 mg/kg   | -         |
| Marine water sediment  |                        | 3.04 mg/kg   | -         |
| Soil                   |                        | 29.5 mg/kg   | -         |
| Sewage Treatment Plant |                        | 100 mg/l     | -         |
| ethylbenzene           | Fresh water            | 0.1 mg/l     | -         |
|                        | Marine water           | 0.01 mg/l    | -         |
|                        | Fresh water sediment   | 13.7 mg/kg   | -         |
|                        | Marine water sediment  | 1.37 mg/kg   | -         |
|                        | Soil                   | 2.68 mg/kg   | -         |
|                        | Sewage Treatment Plant | 9.6 mg/l     | -         |
| toluene                | Fresh water            | 0.68 mg/l    | -         |
|                        | Marine water           | 0.68 mg/l    | -         |
|                        | Fresh water sediment   | 16.39 mg/l   | -         |
|                        | Marine water sediment  | 16.39 mg/l   | -         |
|                        | Soil                   | 2.89 mg/kg   | -         |
|                        | Sewage Treatment Plant | 13.61 mg/l   | -         |

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: chemical splash goggles and/or face shield.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 foil  $\geq$  0.7 mm  
4 - 8 hours (breakthrough time): Recommended EN 374 neoprene  $\geq$  0.7 mm  
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR ( $\geq$  0.35 mm). Only suitable as splash protection. Only

**SECTION 8: Exposure controls/personal protection**

suitable for brief exposure. In the event of contamination, change protective gloves immediately.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Cotton or cotton/synthetic overalls or coveralls are normally suitable.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: EN 405:2001 + A1:2009 organic vapour (Type A) and particulate filter FFA2P3 R D
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Liquid.
- Colour** : Not available.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : 56°C
- Flash point** : Closed cup: 5°C
- Evaporation rate** : Not available.
- Upper/lower flammability or explosive limits** : Not available.
- Vapour pressure** : Not available.
- Vapour density** : Not available.
- Relative density** : 0.922
- Solubility(ies)** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/ water** : Not available.

## SECTION 9: Physical and chemical properties

|                                  |                  |
|----------------------------------|------------------|
| <b>Auto-ignition temperature</b> | : Not available. |
| <b>Decomposition temperature</b> | : Not available. |
| <b>Viscosity</b>                 | : Not available. |
| <b>Explosive properties</b>      | : Not available. |
| <b>Oxidising properties</b>      | : Not available. |

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

|  |  |
|--|--|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.                                     |
| <b>10.2 Chemical stability</b>                 | : Stable under recommended storage and handling conditions (see Section 7).  |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.  |
| <b>10.4 Conditions to avoid</b>                | : When exposed to high temperatures may produce hazardous decomposition products.  |
| <b>10.5 Incompatible materials</b>             | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| <b>10.6 Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.                           |

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Acute toxicity

**SECTION 11: Toxicological information**

| Product/ingredient name | Result                 | Species | Dose         | Exposure |
|-------------------------|------------------------|---------|--------------|----------|
| 2-butoxyethyl acetate   | LC50 Inhalation Vapour | Rat     | >3.91 mg/l   | 4 hours  |
|                         | LD50 Dermal            | Rabbit  | 1500 mg/kg   | -        |
|                         | LD50 Oral              | Rat     | 1880 mg/kg   | -        |
| n-butyl acetate         | LC50 Inhalation Vapour | Rat     | >21.1 mg/l   | 4 hours  |
|                         | LD50 Dermal            | Rabbit  | >14112 mg/kg | -        |
|                         | LD50 Oral              | Rat     | 10760 mg/kg  | -        |
| xylene                  | LC50 Inhalation Vapour | Rat     | 27.6 mg/l    | 4 hours  |
|                         | LD50 Dermal            | Rabbit  | >2000 mg/kg  | -        |
|                         | LD50 Oral              | Rat     | >2000 mg/kg  | -        |
| acetone                 | LC50 Inhalation Vapour | Rat     | 76 mg/l      | 4 hours  |
|                         | LD50 Dermal            | Rabbit  | >15800 mg/kg | -        |
|                         | LD50 Oral              | Rat     | 5800 mg/kg   | -        |
| ethylbenzene            | LC50 Inhalation Vapour | Rat     | >9.6 mg/l    | 4 hours  |
|                         | LD50 Dermal            | Rabbit  | >15000 mg/kg | -        |
|                         | LD50 Oral              | Rat     | >3500 mg/kg  | -        |
| toluene                 | LC50 Inhalation Vapour | Rat     | 28.1 mg/l    | 4 hours  |
|                         | LD50 Dermal            | Rabbit  | >5000 mg/kg  | -        |
|                         | LD50 Oral              | Rat     | 5580 mg/kg   | -        |

**Conclusion/Summary** : Not available.

**Acute toxicity estimates**

| Route                | ATE value    |
|----------------------|--------------|
| Dermal               | 4291.9 mg/kg |
| Inhalation (vapours) | 11.8 mg/l    |

**Irritation/Corrosion**

| Product/ingredient name | Result                   | Species | Score | Exposure                   | Observation |
|-------------------------|--------------------------|---------|-------|----------------------------|-------------|
| 2-butoxyethyl acetate   | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams    | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 500 milligrams             | -           |
| xylene                  | Skin - Mild irritant     | Rat     | -     | 8 hours 60 microliters     | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams    | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 100 Percent                | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 87 milligrams              | -           |
| acetone                 | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 milligrams      | -           |
|                         | Eyes - Mild irritant     | Human   | -     | 186300 parts per million   | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 10 microliters             | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 20 milligrams     | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 20 milligrams              | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams    | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 395 milligrams             | -           |
| ethylbenzene            | Eyes - Severe irritant   | Rabbit  | -     | 500 milligrams             | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 15 milligrams     | -           |
| toluene                 | Eyes - Mild irritant     | Rabbit  | -     | 0.5 minutes 100 milligrams | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 870 Micrograms             | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 2                 | -           |

**SECTION 11: Toxicological information**

|  |                          |        |   |                            |   |
|--|--------------------------|--------|---|----------------------------|---|
|  | Skin - Mild irritant     | Pig    | - | milligrams<br>24 hours 250 | - |
|  | Skin - Mild irritant     | Rabbit | - | microliters<br>435         | - |
|  | Skin - Moderate irritant | Rabbit | - | milligrams<br>24 hours 20  | - |
|  | Skin - Moderate irritant | Rabbit | - | milligrams<br>500          | - |

**Conclusion/Summary** : Not available.

**Sensitisation**

**Conclusion/Summary** : Not available.

**Mutagenicity**

**Conclusion/Summary** : Not available.

**Carcinogenicity**

**Conclusion/Summary** : Not available.

**Reproductive toxicity**

**Conclusion/Summary** : Not available.

**Teratogenicity**

**Conclusion/Summary** : Not available.

**Specific target organ toxicity (single exposure)**

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| n-butyl acetate         | Category 3 | Not applicable.   | Narcotic effects             |
| xylene                  | Category 3 | Not applicable.   | Respiratory tract irritation |
| acetone                 | Category 3 | Not applicable.   | Narcotic effects             |
| toluene                 | Category 3 | Not applicable.   | Narcotic effects             |

**Specific target organ toxicity (repeated exposure)**

| Product/ingredient name | Category   | Route of exposure | Target organs  |
|-------------------------|------------|-------------------|----------------|
| xylene                  | Category 2 | Not determined    | Not determined |
| ethylbenzene            | Category 2 | Not determined    | hearing organs |
| toluene                 | Category 2 | Not determined    | Not determined |

**Aspiration hazard**

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |
| toluene                 | ASPIRATION HAZARD - Category 1 |

**Other information** : Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

**SECTION 12: Ecological information**

| Product/ingredient name | Result                  | Species                                 | Exposure |
|-------------------------|-------------------------|---|----------|
| 2-butoxyethyl acetate   | Acute EC50 1570 mg/l    | Algae - Pseudokirchneriella subcapitata | 72 hours |
| n-butyl acetate         | Acute EC50 37 mg/l      | Daphnia - Daphnia magna                 | 48 hours |
|                         | Acute LC50 22 mg/l      | Fish - Pimephales promelas              | 96 hours |
| xylene                  | Acute EC50 647.7 mg/l   | Algae - Desmodesmus subspicatus         | 72 hours |
|                         | Acute EC50 44 mg/l      | Daphnia                                 | 48 hours |
|                         | Acute LC50 32 mg/l      | Crustaceans - Artemia salina            | 48 hours |
|                         | Acute LC50 18 mg/l      | Fish - Pimephales promelas              | 96 hours |
|                         | Acute NOEC 200 mg/l     | Algae                                   | 72 hours |
|                         | Chronic NOEC 23 mg/l    | Daphnia - Daphnia magna                 | 21 days  |
| acetone                 | Acute EC50 1 to 10 mg/l | Algae                                   | 72 hours |
|                         | Acute EC50 1 to 10 mg/l | Daphnia - Daphnia magna                 | 48 hours |
|                         | Acute LC50 1 to 10 mg/l | Fish                                    | 96 hours |
| ethylbenzene            | Acute EC50 8800 mg/l    | Daphnia - Daphnia pulex                 | 48 hours |
|                         | Acute LC50 5540 mg/l    | Fish - Oncorhynchus mykiss              | 96 hours |
|                         | Acute NOEC 430 mg/l     | Algae                                   | 96 hours |
|                         | Chronic NOEC 2212 mg/l  | Daphnia - Daphnia pulex                 | 28 days  |
| toluene                 | Acute EC50 >1.8 mg/l    | Daphnia - Daphnia magna                 | 48 hours |
|                         | Acute LC50 >10 mg/l     | Fish - Pimephales promelas              | 96 hours |
|                         | Acute EC50 12.5 mg/l    | Algae                                   | 72 hours |
|                         | Acute EC50 3.8 mg/l     | Daphnia - Daphnia magna                 | 48 hours |
|                         | Acute LC50 5.5 mg/l     | Fish - Oncorhynchus kisutch             | 96 hours |

**Conclusion/Summary** : Not available.

**12.2 Persistence and degradability**

| Product/ingredient name | Test  | Result         | Dose | Inoculum |
|-------------------------|---|----------------|------|----------|
| n-butyl acetate         | OECD 301D Ready Biodegradability - Closed Bottle Test | >80 % - 5 days | -    | -        |

**Conclusion/Summary** : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis       | Biodegradability |
|-------------------------|-------------------|------------------|------------------|
| 2-butoxyethyl acetate   | -                 | 90.4%; 28 day(s) | -                |
| n-butyl acetate         | -                 | -                | Readily          |
| toluene                 | -                 | -                | Readily          |

**12.3 Bioaccumulative potential**

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| 2-butoxyethyl acetate   | 1.51               | -           | low       |
| n-butyl acetate         | 2.3                | -           | low       |
| xylene                  | 3.12               | 8.1 to 25.9 | low       |
| acetone                 | -0.23              | -           | low       |
| ethylbenzene            | 3.6                | -           | low       |
| toluene                 | 2.73               | 90          | low       |

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

## SECTION 12: Ecological information

- PBT** : Not applicable.  
**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### Packaging





**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

| Type of packaging     | European waste catalogue (EWC)  |
|-----------------------|---|
| CEPE Paint Guidelines | 15 01 10*<br>packaging containing residues of or contaminated by hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID  | ADN  | IMDG  | IATA   |
|--|--|--|---|--|
| <b>14.1 UN number</b>                  | UN1263   | UN1263   | UN1263  | UN1263   |
| <b>14.2 UN proper shipping name</b>    | PAINT RELATED MATERIAL   | PAINT RELATED MATERIAL   | PAINT RELATED MATERIAL  | Paint related material   |
| <b>14.3 Transport hazard class(es)</b> | 3<br> | 3<br> | 3<br> | 3<br> |

## SECTION 14: Transport information

|                                   |  |   |   |  |
|-----------------------------------|--|---|---|--|
| <b>14.4 Packing group</b>         | II   | II  | II  | II   |
| <b>14.5 Environmental hazards</b> | No.  | No.   | No.   | No.  |
| <b>Additional information</b>     | <p><b>Hazard identification number</b><br/>33</p> <p><b>Limited quantity</b><br/>5 L</p> <p><b>Special provisions</b><br/>163, 640C, 650</p> <p><b>Tunnel code</b><br/>(D/E)</p> | <p><b>Special provisions</b><br/>163, 640C, 650</p> | <p><b>Emergency schedules (EmS)</b><br/>F-E, _S-E_</p> <p><b>Special provisions</b><br/>163</p> | <p><b>Passenger and Cargo Aircraft</b><br/>Quantity limitation: 5 L<br/>Packaging instructions: 353</p> <p><b>Cargo Aircraft Only</b><br/>Quantity limitation: 60 L<br/>Packaging instructions: 364</p> <p><b>Limited Quantities - Passenger Aircraft</b><br/>Quantity limitation: 1 L<br/>Packaging instructions: Y341</p> <p><b>Special provisions</b><br/>A3, A72</p> |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Other EU regulations**

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**Europe inventory** : All components are listed or exempted.

**Industrial emissions (integrated pollution prevention and control) - Air** : Listed

**SECTION 15: Regulatory information**

| Product/ingredient name | Carcinogenic effects | Mutagenic effects | Developmental effects            | Fertility effects |
|-------------------------|----------------------|-------------------|----------------------------------|-------------------|
| toluene                 | -                    | -                 | Repr. 2, H361d<br>(Unborn child) | -                 |

**Ozone depleting substances (1005/2009/EU)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Seveso Directive**

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

**Industrial use**

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**International regulations****Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol (Annexes A, B, C, E)**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

**International lists****National inventory**

- Australia** : All components are listed or exempted.  
**Canada** : All components are listed or exempted.  
**China** : All components are listed or exempted.  
**Japan** : **Japan inventory (ENCS)**: All components are listed or exempted.  
**Japan inventory (ISHL)**: All components are listed or exempted.  
**Malaysia** : Not determined.  
**New Zealand** : All components are listed or exempted.  
**Philippines** : All components are listed or exempted.  
**Republic of Korea** : All components are listed or exempted.  
**Taiwan** : All components are listed or exempted.  
**Turkey** : All components are listed or exempted.  
**United States** : All components are listed or exempted.

**15.2 Chemical safety assessment**

: No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information****CEPE code** : 1

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

| Classification  | Justification   |
|---|---|
| Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336 | On basis of test data<br>Calculation method<br>Calculation method |

**Full text of abbreviated H statements**

|                       |   |
|-----------------------|---|
| H225                  | Highly flammable liquid and vapour.   |
| H226                  | Flammable liquid and vapour.  |
| H304                  | May be fatal if swallowed and enters airways.                                       |
| H312                  | Harmful in contact with skin.   |
| H315                  | Causes skin irritation.   |
| H319                  | Causes serious eye irritation.  |
| H331                  | Toxic if inhaled.   |
| H332                  | Harmful if inhaled.   |
| H335                  | May cause respiratory irritation.   |
| H336                  | May cause drowsiness or dizziness.  |
| H361d (Unborn child)  | Suspected of damaging the unborn child.   |
| H373 (hearing organs) | May cause damage to organs through prolonged or repeated exposure. (hearing organs) |
| H373                  | May cause damage to organs through prolonged or repeated exposure.                  |
| H412                  | Harmful to aquatic life with long lasting effects.                                  |

**Full text of classifications [CLP/GHS]**

|                                  |  |
|----------------------------------|--|
| Acute Tox. 3, H331               | ACUTE TOXICITY (inhalation) - Category 3   |
| Acute Tox. 4, H312               | ACUTE TOXICITY (dermal) - Category 4   |
| Acute Tox. 4, H332               | ACUTE TOXICITY (inhalation) - Category 4   |
| Aquatic Chronic 3, H412          | LONG-TERM AQUATIC HAZARD - Category 3  |
| Asp. Tox. 1, H304                | ASPIRATION HAZARD - Category 1   |
| EUH066                           | Repeated exposure may cause skin dryness or cracking.  |
| Eye Irrit. 2, H319               | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2   |
| Flam. Liq. 2, H225               | FLAMMABLE LIQUIDS - Category 2   |
| Flam. Liq. 3, H226               | FLAMMABLE LIQUIDS - Category 3   |
| Repr. 2, H361d (Unborn child)    | REPRODUCTIVE TOXICITY (Unborn child) - Category 2  |
| Skin Irrit. 2, H315              | SKIN CORROSION/IRRITATION - Category 2   |
| STOT RE 2, H373 (hearing organs) | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (hearing organs) - Category 2             |
| STOT RE 2, H373                  | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2                              |
| STOT SE 3, H335                  | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3 |
| STOT SE 3, H336                  | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3             |

**Full text of abbreviated R phrases**

## SECTION 16: Other information

R11- Highly flammable.

R10- Flammable.

R63- Possible risk of harm to the unborn child.

R20- Harmful by inhalation.

R20/21- Harmful by inhalation and in contact with skin.

R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65- Harmful: may cause lung damage if swallowed.

R36- Irritating to eyes.

R38- Irritating to skin.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

### [Full text of classifications \[DSD/DPD\]](#)

F - Highly flammable

Repr. Cat. 3 - Toxic to reproduction category 3

Xn - Harmful

Xi - Irritant

**Date of printing** : 21/02/2018

**Date of issue/ Date of revision** : 20/02/2018

**Date of previous issue** : 14/12/2017

**Version** : 1.4

### [Notice to reader](#)

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.