

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: DeWipe-Outs™ Pre-saturated Wipes containing Low VOC Cleaner
Part Number: DeVilbiss Automotive Refinishing Part No. 803418
Product Description: Lint-free, pre-saturated prep wipe.
SDS #: SDS-60 REVISION #: 7-21-2015
Chemical Formula: Proprietary Wipe fabric, Acetone, Isopropyl Alcohol, Dipropylene Glycol Monomethyl Ether, and Deionized Water.
CAS Number: See Section #3, below
Article Code: 3215
General Use: Use this wipe to clean and remove dust, dirt, residue, and static from surfaces to be painted.

Company Information:
DeVilbiss Automotive Refinishing
11360 S. Airfield Rd.
Swanton, Ohio 43558
Customer Service Phone: 1-800-445-3988

Emergency telephone number - CHEMTREC (24 HOURS): 1-800-424-9300

2. HAZARDS IDENTIFICATION

Label elements
Hazard pictograms:



Signal word: DANGER!

GHS Class: Flammable liquid, Category 2
Eye Irritant, Category 2
Specific Target Organ Toxicity, Single Exposure, Category 3

Hazard statements: H225 – Highly flammable liquid and vapor.
H319 – Causes serious eye irritation.
H336 – May cause drowsiness or dizziness.

Precautionary statements: P210 – Keep away from heat/sparks/open flames – No smoking.
P243 – Take precautionary measures against static discharge.
P370 – IN CASE OF FIRE: Use dry chemical, carbon dioxide to extinguish small fires. Use water for large fires.
P280 – Wear protective gloves/protective clothing/eye protection/face protection.
P261 – Avoid breathing vapors.
P403 + 233 – Store in a well-ventilated place. Keep container tightly closed.
P501 – Dispose of contents/container in accordance with Local, State, Federal, and Provincial regulations.
P305 – IF IN EYES: Rinse cautiously with water for several minutes.

P304 – IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 – Call a POISON CONTROL CENTER or doctor/physician if you feel unwell.

P303 = 361 + 353 – IF ON SKIN OR HAIR: Remove/Take off all contaminated clothing immediately. Rinse skin with water or shower.

Emergency Overview:	Warning! Flammable. Irritant. May cause drowsiness or dizziness.
Route of Exposure:	Eyes. Skin. Inhalation.
Potential Health Effects	
Eye contact:	Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage, and permanent injury.
Skin contact:	May cause skin irritation; itching, redness, rashes, hives, burning, and swelling.
Inhalation:	Inhalation of vapors, fumes, or mists of the product may be irritating to the respiratory system. Excessive exposure may cause dizziness, headache, and anesthetic effects.
Ingestion:	May cause irritation; a burning sensation of the mouth, throat, and gastrointestinal tract, and abdominal pain.
Chronic Effects:	Prolonged or repeated contact may cause burning associated with severe reddening, swelling, and possible tissue destruction.
Signs and Symptoms:	Overexposure may cause headaches, dizziness, nausea, and vomiting.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system. Central nervous system.
Medical Conditions Aggravated by Long-Term Exposure:	Individuals with pre-existing skin disorders, asthma, allergies, or known sensitization may be more susceptible to the effects of this product.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	% Vol	CAS Number	EC Number
Acetone	75	67-64-1	200-662-2
Isopropyl Alcohol	2	67-63-0	200-661-7
Dipropylene Glycol Monomethyl Ether	1	34590-94-8	252-104-2
Deionized Water	22	7732-18-5	231-791-2

4. FIRST-AID MEASURES

Description of first aid measures

Eye Contact:	IF IN EYES: Immediately rinse with water for at least 15-20 minutes. Remove contact lenses, if present and easy to do. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Seek immediate medical attention.
Inhalation:	IF INHALED: Remove victim to fresh air and keep at rest in a comfortable position for breathing. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

- Skin Contact:** IF ON SKIN OR HAIR: Remove/take off all contaminated clothing. Immediately wash skin with plenty of soap and water for 15-20 minutes. If skin irritation develops or persists, seek medical attention.
- Ingestion:** IF SWALLOWED: Do NOT induce vomiting. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration. Call the POISON CONTROL CENTER or a doctor/physician immediately. Never give anything by mouth to an unconscious person.
- Other First Aid:** Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested.

5. FIRE-FIGHTING MEASURES

- Flash Point:** 13.3°C / 56°F.
Autoignition Temperature: 465°C / 837°F.
Lower Flammable/Explosive Limit: 2.5% by volume
Upper Flammable/Explosive Limit: 7.0% by volume
Suitable extinguishing media: Use dry chemical or carbon dioxide.
- Protective equipment:** In the event of a fire, wear appropriate full protective gear and a Self-Contained Breathing Apparatus (SCBA) in accordance with NIOSH, NFPA, and/or EN 137 guidelines, with a full face-piece operated in positive pressure mode.
- Fire Fighting Instructions:** Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers in order to minimize risk of rupture. Do not enter confined space without full protective gear. If possible, contain fire run-off water.
- NFPA Rating:** Health: 2
Flammability: 3
Instability: 0
- HMIS Rating:** See Section 15.



6. ACCIDENTAL RELEASE MEASURES

- Personnel Precautions:** Evacuate the area and keep unnecessary and unprotected personnel from entering the spill area.
- Environmental precautions:** Avoid runoff into storm sewers, ditches, and waterways. Comply with all governmental regulations regarding the reporting of chemical releases.
- Methods for containment:** Spills are very unlikely, because the wiper fabric has absorbed the liquid solvent solution. In the event of a spill, contain with an inert absorbent material.
- Methods for Cleanup:** Absorb spill with an inert material (e.g., dry sand or earth), then place into a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue.
- Material is flammable. Eliminate ignition sources. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and

flash back. Ventilate area. Use proper personal protective equipment as listed in section 8.

7. HANDLING AND STORAGE

- Handling:** Use with adequate ventilation. Avoid breathing vapors, aerosol, or mist. Use only in accordance with the directions. Do not reuse containers without proper cleaning or reconditioning.
- Storage:** Store in a cool, dry, well-ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible substances. Keep container tightly closed when not in use.
- Protective measures:** Wash thoroughly after handling.
- Special Handling Procedures:** Hazardous liquid or vapor residue may remain in emptied container. Do not reuse, heat, burn, pressurize, cut, weld, braze, solder, drill, grind, expose to sparks / flame / other ignition sources without proper cleaning and reconditioning.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters Exposure Guidelines:

Acetone:

ACGIH:	TLV-TWA:	500 ppm
	TLV-STEL:	750 ppm
OSHA:	PEL-TWA:	1000 ppm

Isopropyl Alcohol:

ACGIH:	TLV-TWA:	200 ppm
	TLV-STEL:	400 ppm
OSHA:	PEL-TWA:	400 ppm

Dipropylene Glycol Monomethyl Ether:

ACGIH:	TLV-TWA:	100 ppm
	TLV-STEL:	150 ppm
	Skin:	Yes
OSHA:	PEL-TWA:	100 ppm
	PEL-STEL:	150 ppm
	Skin:	Yes

Exposure controls

- Appropriate engineering:** Use appropriate engineering control measures such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Where such systems are not effective wear suitable personal protective equipment which performs satisfactorily and meets OSHA or other recognized standards. Consult with local professionals for selection, training, inspection, and maintenance of the personal protective equipment.

Personal Protection Equipment

- Eye Protection:** Safety glasses with side shields must be worn at all times. If splash hazard exists, wear chemical splash goggles and/or face shield.
- Skin Protection:** Wear appropriate chemically resistant gloves and other apparel to prevent skin contact. Consult glove manufacturer for permeability data.
- Respiratory Protection:** Use a NIOSH/MSHA or European Std. EN 149 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced. Comply with OSHA respirator regulations found in 29 CFR 1910.134 or European Std. EN 149. Use a positive pressure supplied air respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any circumstances where air purifying respirators may not provide adequate protection.

Other Protective:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

PPE Pictograms:

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

Physical state:	Solid with impregnated liquid
Color:	White wipe, colorless liquid.
Odor:	Like acetone / nail polish remover.
Appearance:	Looks like a wet cloth.
pH:	Neutral
Freezing point:	Not determined
Boiling point:	69.4°C (157°F).
Flash point:	13.3°C / 56°F.
Flammability (solid, gas):	Highly flammable.
Upper/lower flammability or explosive limits:	No data.
Vapor pressure:	not determined
Vapor density:	1.5 (water = 1.0)
Evaporation Rate:	4 (water = 1)
Percent volatile	100%
Relative density:	Not determined
Solubility in Water:	Soluble in water.
Partition coefficient n-octanol/water:	No data.
Auto-ignition temperature:	465°C / 837°F.
Decomposition temperature:	No data.
Viscosity:	Not determined
Specific gravity (water=1):	0.862 g/cm ³ @20°C (68°F)

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal temperatures and pressures.
Hazardous polymerization:	Not reported.
Conditions to avoid:	Keep away from heat, sparks, open flame, and other ignition sources. Avoid incompatible materials, oxidizers, and oxidizing conditions.
Incompatible materials:	Oxidizing agents. Strong acids and alkalis.

11. TOXICOLOGICAL INFORMATION

Acetone

Eye:

Eye – Human Std. Draize Test:	500 ppm
Eye – Rabbit Std. Draize Test:	20 mg/24 hrs.
Eye – Rabbit Std. Draize Test:	10µL
Eye – Human Std. Draize Test:	186,300 ppm
Eye – Rabbit Std. Draize Test:	20 mg

Skin:

Administration onto the skin – Rabbit:	20 mL/kg
Administration onto the skin – Guinea Pig:	>9400 µL/kg [Details of toxic effects not reported other than lethal dose value]
Administration onto the skin – Mouse:	31.6 µg/kg/2W (intermittent) [Biochemical – Metabolism (intermediary) - Other]
Administration onto the skin – Rabbit:	395 mg
Administration onto the skin – Rabbit:	500 mg/24H

Inhalation:

Inhalation – Rat LC50: 50100 mg/m³ [Details of toxic effects not reported other than lethal dose value]

Inhalation – Rat LC50: 50100 mg/m³/8H [Details of toxic effects not reported other than lethal dose value]

Inhalation – Mouse LC50: 44 mg/m³/4H [Details of toxic effects not reported other than lethal dose value]

Ingestion:

Oral – Rat LD50: 5800 mg/kg [Details of toxic effects not reported other than lethal dose value]

Oral – Rat LD50: 5800 mg/kg [Behavioral: Altered sleep time (including change in righting reflex), Behavioral: Tremor]

Oral – Mouse LD50: 3 mg/kg [Details of toxic effects not reported other than lethal dose value]

Isopropyl Alcohol

Eye contact:

Eye – Rabbit Std. Draize Test: 100 mg

Eye – Rabbit Std. Draize Test: 10 mg

Eye – Rabbit Std. Draize Test: 100 mg/24 hr. (RTECS)

Skin contact:

Administration onto the skin – Rabbit Std. Draize Test: 500 mg

Administration onto the skin – Rabbit LD50: 12800 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Inhalation:

Inhalation – Rat LC50: 16000 ppm/8 hr. [Details of toxic effects not reported other than lethal dose value]

Inhalation – Mouse LC50: 53000 mg/m³ [Behavioral: General anesthetic Lungs, Thorax, or Respiration – Other changes]

Inhalation – Rat LC50: 72600 mg/m³ [Behavioral: General anesthetic Lungs, Thorax, or Respiration – Other changes] (RTECS)

Ingestion:

Oral – Rat LD50: 5045 mg/kg [Behavioral: Altered sleep time (including change in righting reflex), Behavioral: Somnolence (general depressed activity)]

Oral – Mouse LD50: 3600 mg/kg [Behavioral: Altered sleep time (including change in righting reflex), Behavioral: Somnolence (general depressed activity)]

Oral – Mouse LD50: 3600 mg/kg [Behavioral: General anesthetic]

Oral – Rat LD50: 5000 mg/kg [Behavioral: General anesthetic] (RTECS)

Skin contact:

Administration onto the skin – Rabbit Std. Draize Test: 500 mg

Administration onto the skin – Rabbit LD50: 12800 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

reported other than lethal dose value] (RTECS)

Dipropylene Glycol Monomethyl Ether

Eye: Eye – Rabbit Std. Draize Test: 500 mg/24 hrs.

Skin: Skin – Rabbit Open Irritation Test: 500mg [mild] (RTECS)
Skin – Rabbit LD50: 10mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Ingestion: Oral – Rat LD50: 5.5 mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

12. ECOLOGICAL INFORMATION

Complete Product

Ecotoxicity: No ecotoxicity data is available.
Environmental Fate: No environmental fate data is available.

Isopropyl Alcohol

Ecotoxicity: LC50; Species: 1,400,000 µg/L for 48 hr. – Species: Crangon crangon (Common Shrimp)
LC50; 10,000,000 µg/L for 24 hr. – Species: Daphnia magna (Water Flea)
LD50; >5000 mg/L for 24 hr. – Species: Cassius auratus (Goldfish)
LC50; 11,130 mg/L for 48 hr. – Species: Pimephales promelas (Fathead Minnows)

Environmental Fate: Isopropyl Alcohol is expected to have a very high mobility through soil.

Bioaccumulation: Bioconcentration in aquatic organisms is low.

13. DISPOSAL CONSIDERATIONS

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations.

Waste treatment methods

Methods of disposal: Consult with the US EPA guidelines listed in 40 CFR Part 263.1 or the EU Directive 2008/98/EC on waste for the classifications of hazardous waste prior to disposal. Furthermore, consult with your local, regional / provincial / state, national, and international regulations or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance with the EPA and/or state and local guidelines.

Packaging

Special precautions: DANGER! Rags, steel wool, and other waste soaked with this product may spontaneously catch fire if improperly discarded or stored.

Methods of disposal: To avoid a spontaneous combustion fire, immediately after use place any rags, steel wool, or other waste soaked with this product in a sealed, water-filled, metal container.

14. TRANSPORT INFORMATION

DOT Shipping Name: Solids containing flammable liquid, n.o.s. (Acetone, Isopropanol). (Limited quantity).
DOT Hazard Class: 4.1
DOT Packing Group: II

IATA Shipping Name: Solids containing flammable liquid, n.o.s. (Acetone, Isopropanol).
IATA Hazard Class: 4.1
IATA Packing Group: II

IMDG UN Number: UN 3175 (Limited quantity)
IMDG Shipping Name: Solids containing flammable liquid, n.o.s. (Acetone, Isopropanol). (Limited quantity).
IMDG Hazard Class: 4.1
IMDG Packing Group: II

Marine Pollutant: No

15. REGULATORY INFORMATION

Federal Regulations

Canada WHMIS: Controlled – Class: B2 Flammable Liquid
 Controlled – Class: D2B Toxic

Acetone

TSCA Inventory Status: Listed.
SARA: EPCRA – 40 CFR Part 372 – (SARA Title III) Section 313 Listed Chemical
State Regulations: Listed in the State of Massachusetts Hazardous Substance List
 Listed in the New Jersey State Right to Know List
 Listed in the Pennsylvania State Hazardous Substances List

Canada DSL: Listed.
EC Number: 200-662-2

Isopropyl Alcohol

TSCA Inventory Status: Listed.
Canada DSL: Listed.
EC Number: 200-661-7

Dipropylene Glycol Monomethyl Ether

TSCA Inventory Status: Listed.
Canada DSL: Listed.
EC Number: 252-104-2

Deionized Water

EC Number: 231-791-2

Canadian Regulations: WHMIS Hazard Classes: B2
 All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms:



HMIS RATING: Health = 2
 Flammability = 3
 Reactivity = 0
 Personal Protection = X



16. OTHER INFORMATION

Date Revised: 07/21/2015
Date Prepared: 07/21/2015

SDS PREPARED BY: Director of Chemical Safety

The information contained herein is based on data available to us and is accurate and reliable to the best of our knowledge and belief. However, DeVilbiss makes no representations as to its completeness or accuracy. Information is supplied on condition that persons receiving such information will make their own determination as to its suitability for their purposes prior to use. In no event will DeVilbiss be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

*** END OF SDS ***

©2015 Carlisle Fluid Technologies, Inc., dba Finishing Brands. All rights reserved.
DeVilbiss is part of Finishing Brands, a global leader of innovative spray finishing technologies.