

# SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2024 / Canada WHMIS 2023



Date issued : 05/01/2025

SDS number : SAPBUS 3 IN 1 Primer Black 454g\_EN

Date revised : 05/01/2025

Revision number : 1

## SAPBUS 3 IN 1 Primer Black, aerosol

### 1. Identification

**Product identifier:** SAPBUS 3 IN 1 Primer Black, aerosol

**Product description:** Black Primer, vehicle refinishing product , aerosol coating 16 oz (1 lb) 454 g

**Relevant identified uses of the substance or mixture and uses advised against:** Aerosol Coating, Automotive Use Only

**Other means of identification - product Stock / Code:** SAPBUS / 54025

**Chemical family:** Modified nitrocellulose coating

**Molecular formula:** Mixture

#### Manufacturer / Supplier

Dominion Sure Seal Ltd.  
6175 Danville Road, Mississauga  
Ontario, Canada L5T 2H7  
Fax: 905-670-5174  
www.dominionsureseal.com

**Customer Service:** 905-670-5411

#### Emergency telephone number

Telephone number to contact in the event of an emergency (9 am to 5 pm from M to F):  
(905) 670-5411

### 2. Hazard identification

#### Classification of the substance or mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2024) and the Canadian WHMIS regulations (Hazardous Products Regulations; WHMIS 2023). This information may be different from the actual product label information for labels that are regulated by other agencies.

#### Health hazards:

Eye Irritation, Category 2  
Skin Sensitization, Category 1  
Specific Target Organ Toxicity (Single exposure), Category 3 (Narcotic Effects)  
Specific Target Organ Toxicity (Repeated exposure), Category 2  
Carcinogenicity, Category 1B

#### Physical hazards:

Aerosols, Category 1  
Simple Asphyxiants, Category 1

#### Label elements

Hazardous components for labelling:

**n-butyl acetate, acetone, talc, maleated rosin, polymer with glycerol, 2-methoxy-1-methylethyl acetate, stoddard solvent, carbon black, nitrocellulose resin, isopropyl alcohol and solvent naphtha light aliphatic**



Flame



Exclamation  
mark



Health  
hazard

**Signal word:** DANGER

**Hazard statement(s)**

H222: Extremely flammable aerosol.

H229: Pressurized container: may burst if heated.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H373: May cause damage to central nervous system, kidneys and liver through prolonged or repeated exposure.

H350: May cause cancer by dust inhalation.

H600: May displace oxygen and cause rapid suffocation.

**Precautionary statement(s)**

**Supplemental label elements:**

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Prevention:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P264: Wash hands thoroughly after handling.

P260: Do not breathe mist, vapours or spray.

P261: Avoid breathing dust.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves and eye protection.

**Response:**

P308+P313: IF exposed or concerned: Get medical advice/attention.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage:**

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

**Disposal:**

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

**Hazards not otherwise classified:** No data available.

**Emergency overview**

## SAPBUS 3 IN 1 Primer Black, aerosol

**Immediate concerns:** Extremely flammable aerosol. Causes serious eye irritation. Prolonged and repeated skin contact may lead to slight transient irritation in sensitive individuals. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Vapours may cause drowsiness and dizziness. Prolonged or repeated exposure may cause central nervous system, kidney and liver damage. Suspected of causing cancer. Vapor reduces oxygen availability for breathing.

**Comments:** See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial / professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2023 and OSHA Hazcom 2024 Hazard Communication labeling.

### 3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
n-butyl acetate	34 - 36	123-86-4
acetone	24 - 26	67-64-1
propane	12 - 14	74-98-6
isobutane	7 - 8	75-28-5
talc	6.5 - 7.5	14807-96-6
maleated rosin, polymer with glycerol	2 - 3	68038-41-5
2-methoxy-1-methylethyl acetate	1.5 - 2.5	108-65-6
stoddard solvent	1.5 - 2.5	8052-41-3
carbon black	1 - 2	1333-86-4
nitrocellulose resin	0.5 - 1.5	9004-70-0
isopropyl alcohol	0.3 - 0.7	67-63-0
solvent naphtha light aliphatic	0.3 - 0.7	64742-89-8
phosphoric acid	0.2 - 0.4	7664-38-2
crystalline silica, quartz	< 0.1	14808-60-7

**Comments:** The actual concentration is withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

talc is a complex substance i.e. complex mixture of known or unknown composition.

crystalline silica, quartz is a hazardous constituent that may be contained in the complex substance at 1% w/w.

### 4. First-aid measures

**Eye:** In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention, if irritation persists.

**Skin:** Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

**Ingestion:** If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**Most important symptoms and effects, both acute and delayed**

**Eye:** Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**Skin:** Substance does not generally irritate and is only mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

**Ingestion:** Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

**Inhalation:** High vapor or spray mist concentrations may be harmful if inhaled. Prolonged or excessive inhalation may cause respiratory tract irritation. May cause headaches and dizziness. High vapor concentrations may cause drowsiness. High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

**Indication of immediate medical attention and special treatment needed, if necessary:** Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

**Additional information:** No data available.

**5. Fire-fighting measures**

**General hazard:** Extremely flammable aerosol. Can readily form explosive mixtures at or above the flash point. Product can be ignited by static discharge.

**Suitable extinguishing media:** Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

**Hazardous combustion products:** During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

**Fire fighting procedures:** Containers can build up pressure if exposed to heat (fire).

**Fire fighting equipment:** As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

**Sensitivity to static discharge:** Product is sensitive to static discharge.

**Sensitivity to mechanical impact:** Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120°F (49°C).

**6. Accidental release measures**

**Small spill:** Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

**Environmental precautions**

**Water spill:** Do not flush to sewer.

**Land spill:** Avoid runoff into storm sewers and ditches which lead to waterways.

**Special protective equipment:** Clean up spills immediately, observing precautions in Protective Equipment section 8.

**7. Handling and storage**

**General procedures:** Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

**Precautions for safe handling:** Contents under pressure. Do not expose to heat or store above 120°F (49°C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breath vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

**SAPBUS 3 IN 1 Primer Black, aerosol**

**Conditions for safe storage:** Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

**8. Exposure controls/personal protection****Exposure controls**

Control parameters				
Chemical name	Occupational exposure limit values			
	Type		ppm	mg/m <sup>3</sup>
n-butyl acetate	OSHA PEL	TWA	150	710
		STEL	200	950
	NIOSH REL	TWA	150	710
		STEL	200	950
acetone	OSHA PEL	TWA	1000	2400
	ACGIH TLV	TWA	500	1188
		STEL	750	1782
	NIOSH REL	TWA	250	590
propane	OSHA PEL	TWA	1000	1800
	ACGIH TLV	TWA	1000	--
	NIOSH REL	TWA	1000	1800
isobutane	ACGIH TLV	STEL	1000	--
	NIOSH REL	TWA	800	1900
talc	OSHA PEL	TWA	-- [1]	2 [1]
	ACGIH TLV	TWA	-- [1]	2 [1]
	NIOSH REL	TWA	-- [1]	2 [1]
2-methoxy-1-methylethyl acetate	USA OEL	-	-- [2]	-- [2]
	EU OEL	TWA	50	275
		STEL	100	550
stoddard solvent	OSHA PEL	TWA	500	2900
	ACGIH TLV	TWA	100	572
carbon black	OSHA PEL	TWA	--	3.5
	ACGIH TLV	TWA	-- [3]	3.5 [3]
	NIOSH REL	TWA	--	3.5
isopropyl alcohol	OSHA PEL	TWA	400	980
	ACGIH TLV	TWA	200	491
		STEL	400	984
	NIOSH REL	TWA	400	980
STEL		500	1225	
solvent naphtha light aliphatic	NIOSH REL	TWA	--	350
		STEL	--	1800

**SAPBUS 3 IN 1 Primer Black, aerosol**

phosphoric acid	<b>OSHA PEL</b>	<b>TWA</b>	--	1
	<b>ACGIH TLV</b>	<b>TWA</b>	--	1
		<b>STEL</b>	--	3
	<b>NIOSH REL</b>	<b>TWA</b>	--	1
<b>STEL</b>		--	3	
crystalline silica, quartz	<b>OSHA PEL</b>	<b>TWA</b>	-- [4]	0.10 [4]
		<b>TWA</b>	-- [5]	0.30 [5]
	<b>ACGIH TLV</b>	<b>TWA</b>	--	0.025
	<b>NIOSH REL</b>	<b>TWA</b>	--	0.05

**Footnotes:**

1. Dust - respirable fraction.
2. This material does not have established exposure limits in the USA under OSHA, NIOSH, ACGIH.
3. Inhalable particulate matter.
4. Dust - respirable fraction.
5. Dust - total fraction.

**Appropriate engineering controls:** Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Avoid breathing mists; if general ventilation or local exhaust is inadequate, persons exposed to mists should wear approved breathing devices. If user operations generate dust during sanding of this product, use ventilation to keep exposure to airborne dust below the above exposure limits.

**Individual protection measures, such as personal protective equipment**

**Eye / face protection:** Wear safety glasses with side shields (or goggles).

**Skin:** Wear chemical resistant gloves. Neoprene is recommended. Avoid prolonged or repeated contact with skin.

**Respiratory protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. Respirator type: Air-purifying respirator with an appropriate, government approved, air-purifying filter, cartridge or canister.

**Skin protection - other:** Not applicable for aerosol containers.

**Occupational hygiene practices:** Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

**9. Physical and chemical properties**

**Physical State:** Liquid, without aerosol propellants

**Odour:** Ketone

**Odour threshold:** No data available.

**Appearance:** Aerosol

**Colour:** Black

**pH:** Not Applicable

**% Volatiles:** 85 to 86% w/w

**Flash point:** -18°C Setaflash Closed Cup, acetone [lowest known value of aerosol concentrate]

**Lower explosion limit / flammability limit:** 1.0

**Upper explosion limit / flammability limit:** 12.8

**Explosion limit / flammability limit notes:** Based on data for acetone

**Auto-ignition temperature:** 480°C

## SAPBUS 3 IN 1 Primer Black, aerosol

**Notes:** Based on data for acetone [lowest known value of aerosol concentrate]

**Vapour pressure:** 55 - 65 psig at 20°C

**Relative vapour density:** > 1 (air = 1)

**Initial boiling point and boiling range:** 56°C (acetone) [lowest known value of aerosol concentrate]

**Freezing point:** No data available.

**Melting point:** No data available.

**Decomposition temperature:** No data available.

**Solubility:** Partial

**Partition coefficient n-octanol/water (logarithmic value):** No data available.

**Evaporation rate (n-butyl acetate = 1):** > 1

**Density:** 0.92 - 0.93 g/ml at 20°C

**Notes:** An estimate for the aerosol concentrate density

**Particle characteristics:** No data available.

**Relative density:** No data available.

**Viscosity (kinematic or dynamic):** > 100 cps at 20°C

**VOC content:** ≤ 0.70 g O<sub>3</sub> / g product

**Flammability:** Flammable Liquids

**Comments:**

### Flammability Statement:

The flammability of an aerosol is determined by its flame extension and/or flashback.

<b>Flammability:</b>	Yes
<b>Aerosol Flame Projection:</b>	50 to 60 cm
<b>Flashback:</b>	Yes
<b>Calculated Aerosol Chemical Heat of Combustion, kJ/g</b>	26 to 28

### VOC Compliance Statement

<b>Total Volatiles:</b>	85 - 86% w/w (< 690 g/l)
<b>VOC Content:</b>	60 - 61% w/w (< 490 g/l), less exempts PWR (PWMIR): ≤ 0.70 g O <sub>3</sub> /g product
<b>VOC Regulation:</b>	USA National VOC Emission Standards for Aerosol Coatings - 40CFR PART 59 SUBPART E
<b>Coating Category:</b>	Auto Body Primer
<b>The VOC content meets the 0.95 PWR category limit for Auto Body Primer. USA compliant.</b>	
<b>VOC Regulation:</b>	California - Regulation for Reducing the Ozone from Aerosol Coating Product Emissions - Title 17, California
<b>Coating Category:</b>	Auto Body Primer
<b>The VOC content meets the 0.95 PWMIR category limit for Auto Body Primer. California compliant.</b>	

## 10. Stability and reactivity

**Reactivity:** No

**SAPBUS 3 IN 1 Primer Black, aerosol****Dangerous polymerization:** Not expected to occur.**Chemical stability:** Stable.**Conditions to avoid:** Keep away from flames and any object that sparks. Container may explode if heated.**Possibility of hazardous reactions:** No data available.**Hazardous decomposition products:** Carbon Monoxide and other toxic vapors.**Incompatible materials:** Oxidizing materials.**11. Toxicological information****Acute Toxicity**

Chemical name	LD <sub>50</sub> (oral) mg/kg (rat)	LD <sub>50</sub> (dermal) mg/kg (rabbit)	LC <sub>50</sub> (inhalation) mg/l
n-butyl acetate	13,100(rat) 11,000(rat)	> 14,400	>45.0(rat;4h)
acetone	8400 5250(mouse) 5300(rabbit)	> 15,700	50.1(rat;8h) 44.0(mouse;4h)
propane	Not Applicable	Not Applicable	>800,000 ppm (rat,15m) [>1443 mg/L]
isobutane	Not Applicable	Not Applicable	658(rat;4h) 570,000 ppm (rat;15m) 680(mouse;2h)
talc	Not classified.	Not classified.	Not classified.
maleated rosin, polymer with glycerol	> 5000	> 5000	No data available.
2-methoxy-1-methylethyl acetate	> 10,000 8532 13,700	>5000(rat) >19,400(rbt)	10.8(rat;3h) 23.5(rat;6h) [no deaths]
stoddard solvent	> 5000	> 3000	8.5(rat;8h) >5.5(rat;4h)
carbon black	> 15,400	> 3000	Not Applicable
isopropyl alcohol	4710-5840 4475(mouse) 5030(rabbit)	12,870	51.0(rat;8h) 72.6(rat;4h)
solvent naphtha light aliphatic	> 2000	> 3000	>23(rat;4h) >33;<42(rat;4h)
phosphoric acid	1530	2740	1.69(rat;1h - mist)

**Acute dermal toxicity LD<sub>50</sub>:** Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.**Acute oral toxicity LD<sub>50</sub>:** Based on available ingredient data, the classification criteria for Acute Oral Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.**Acute inhalation toxicity LC<sub>50</sub>:** Based on available ingredient data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture. The calculated ATE is >20 mg/l/4h (vapours) and >5 mg/l/4h (mists). High vapor concentrations may be harmful if inhaled. Excessive vapor concentrations are attainable. Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation.

## SAPBUS 3 IN 1 Primer Black, aerosol

**Notes:** <5 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

No additional toxicology information is available for this product itself.

(See Component Toxicity Information).

**Information on likely routes of exposure:**

Eye contact. Skin contact. Inhalation.

**Skin corrosion / irritation:** Based on available data, the classification criteria for skin irritation are not met for this mixture. Substance does not generally irritate and is only mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Serious eye damage / irritation:** Contains: acetone, maleated rosin, polymer with glycerol and isopropyl alcohol. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**Respiratory or skin sensitization:** Contains: maleated rosin, polymer with glycerol. May cause sensitization by skin contact. The mixture is classified as: Skin Sensitizer, category 1 based on ingredient data ( $\geq 0.1\%$  ingredients classified as a skin sensitizer, category 1 or sub-category 1A or  $\geq 1.0\%$  ingredients classified as a skin sensitizer, sub-category 1B). Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Based on available data, the classification criteria for respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a respiratory sensitizer, sub-category 1B).

**Germ cell mutagenicity:** Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

### Carcinogenicity

Chemical name	NTP	IARC	OSHA	Status - other
n-butyl acetate	--	--	--	--
acetone	--	--	--	A4 (ACGIH)
propane	--	--	--	--
isobutane	--	--	--	--
talc	--	2A	--	A4 (ACGIH)
maleated rosin, polymer with glycerol	--	--	--	--
2-methoxy-1-methylethyl acetate	--	--	--	--
stoddard solvent	--	--	--	--
carbon black	--	2B	--	A3 (ACGIH)
isopropyl alcohol	--	3	--	--
solvent naphtha light aliphatic	--	--	--	--
phosphoric acid	--	--	--	--
crystalline silica, quartz	K	1	--	A2 (ACGIH)

**Notes:** carbon black is listed as Group 2B (possibly carcinogenic to humans) by IARC. talc is listed as Group 2A (probably carcinogenic to humans) by IARC. Talc: applies only to respirable dust. This product may be sanded during normal conditions of use and there may be potential exposure to respirable dust during such sanding operations. The mixture is classified as: Carcinogenicity, category 1 based on ingredient data using the applicable

## SAPBUS 3 IN 1 Primer Black, aerosol

cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as a Carcinogen, category 1A or 1B).

**Reproductive toxicity:** Contains: toluene. The mixture is classified as: Reproductive Toxicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as Reproductive Toxicity, category 2). May cause adverse reproductive effects. Suspected of damaging the unborn child.

**Specific Target Organ Toxicity - single exposure:** Contains: n-butyl acetate, acetone, 2-methoxy-1-methylethyl acetate, stoddard solvent, isopropyl alcohol and solvent naphtha light aliphatic. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ( $\geq 20\%$  summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3 [Narcotic Effects]). Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

**Specific Target Organ Toxicity - repeated exposure:** Contains: stoddard solvent. The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ( $\geq 1.0\%$  ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). Prolonged or repeated overexposure may cause central nervous system, kidney and liver damage.

**Aspiration hazard:** Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ( $< 10\%$  ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity  $> 20.5 \text{ mm}^2/\text{s}$  at  $40 \text{ }^\circ\text{C}$ ).

## 12. Ecological information

**Ecotoxicological information:** No data available.

**Aquatic toxicity, both acute and chronic:** No data available.

**Persistence and degradability:** No data available.

**Bioaccumulative potential:** No data available.

**Other adverse effects:** No data available.

**Mobility in soil:** No data available.

## 13. Disposal considerations

**Disposal methods:** Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

**Product disposal:** When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

## 14. Transport information

### USA Department of Transport Regulations (DOT)

**UN proper shipping name:** AEROSOLS

**Transport hazard class(es):** 2.1

**UN number:** 1950

**Packing group, if applicable:** N/AP

**DOT other shipping information:**

With an inner packaging  $< 1.0 \text{ L}$ , this product may be shipped as a Limited Quantity as per DOT 173.306.

### IMDG - sea

**UN proper shipping name:** AEROSOLS

**UN number:** 1950

**Transport hazard class(es):** 2.1

**Packing group, if applicable:** N/AP

**SAPBUS 3 IN 1 Primer Black, aerosol****Environmental hazards - marine pollutant:** None**Hazard label:** None**Notes:** With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.**Canadian Transport of Dangerous Goods Regulations (TDG)****UN proper shipping name:** AEROSOLS**UN number:** 1950**Transport hazard class(es):** 2.1**Packing group, if applicable:** N/AP**TDG other shipping information:**

With an inner packaging &lt; 1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

**15. Regulatory information****UNITED STATES****SARA Section 311/312 Hazard Categories****311/312 Health hazards:** Carcinogenicity, Eye Irritation, Narcotic Effects, Simple Asphyxiants, Skin Sensitization, Target Organ Toxicity (Repeated exposure)**311/312 Physical hazards:** Flammable Aerosols**EPCRA Section 302 Extremely Hazardous Substances****EPCRA Status:**

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

**CERCLA Hazardous Substances and Reportable Quantities (RQ)**

Chemical name	% w/w	RQ
n-butyl acetate	34 - 36	5,000
acetone	24 - 26	5,000
phosphoric acid	0.2 - 0.4	5,000


**TSCA (The Toxic Substances Control Act)****TSCA Status:**

All components are included or are otherwise exempt from inclusion on this inventory.

**CAA 112(b) Hazardous Air Pollutants****CAA 112(r) List of Substances for Accidental Release Prevention:**

Name	CAS No.	Threshold Qty (TQ)
Propane	74-98-6	10,000
Butane	75-28-5	10,000

**California Proposition 65:**

 **WARNING:** This product can expose you to chemicals including the chemical(s) listed below, which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SAPBUS 3 IN 1 Primer Black, aerosol**

Chemical name	% w/w	Listed
carbon black	1 - 2	● Cancer
crystalline silica, quartz	< 0.1	● Cancer

**USA OSHA Hazard Communication Standard (29CFR 1910.1200):**

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2024).

**CANADA****WHMIS Hazard Symbol and Classification**

See Section 2 for details.

**WHMIS Regulatory Status:**

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2023).

**WHMIS Classification:**

WHMIS 2023 (Canada) Status: Hazardous Product (See Section 2 for details).

**CEPA - National Pollutant Release Inventory (NPRI):**

Name	CAS No.	NPRI Part No.
n-butyl acetate	123-86-4	5 (VOC)
2-methoxy-1-methylethyl acetate	108-65-6	5 (VOC)
stoddard solvent	8052-41-3	5 (VOC)
isopropyl alcohol	67-63-0	1A, 5 (VOC)
solvent naphtha light aliphatic	64742-89-8	5 (VOC)
propane	74-98-6	5 (VOC)
isobutane	75-28-5	5 (VOC)

**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):**

All components are included or are otherwise exempt from inclusion on this inventory.

**Comments** VOC Content -- See section 9.

**16. Other information**

**Reason for issue:** The Safety Data Sheet was updated.

**Approved by:** Jim Gordon    **Title:** R&D Chemist

**Prepared by :** Regulatory Compliance

**Date revised:** 05/01/2025

**Information contact:** 905-670-5411

**Revision summary:** This SDS replaces the 05/01/2025 SDS.


## SAPBUS 3 IN 1 Primer Black, aerosol

or mixture, Label elements, Precautionary statement(s).

### HMIS RATING

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>B</b>

### NFPA CODES



**NFPA 30 / 30B Storage Classification:** Level 2 Aerosol

**Manufacturer supplemental notes:** None

**Data sources:** Not Available

**Additional SDS Information:** N/AV Not Available

N/AP Not Applicable

ND Not yet determined

ACGIH American Conference of Governmental Industrial Hygienists

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Administration

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

**General statements:** None

**Comments:** None

**Manufacturer disclaimer:** The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.