

Page 1 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 04.10.2021 / 0003  
Replacing version dated / version: 09.12.2020 / 0002  
Valid from: 04.10.2021  
PDF print date: 05.10.2021  
UV Putty Fine  
UV Putty Coarse

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**UV Putty Fine**  
**UV Putty Coarse**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Filler

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

(GB)

Doxa Technological Systems International BV  
Holsteinstraat 16  
8028 RT Zwolle  
The Netherlands  
T +31 38 4676600  
F + 31 38 4676699

Distributor:

Amaric Associates Ltd.  
Richard Jackson  
Wingbury Courtyard Business Village  
HP22 4LW Wingrave, Aylesbury  
+44 (0) 7831 547123  
richard@amaricassociates.co.uk

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+31-38-4676600 (Week days available between 08:00 & 17:00)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.10.2021 / 0003

Replacing version dated / version: 09.12.2020 / 0002

Valid from: 04.10.2021

PDF print date: 05.10.2021

UV Putty Fine

UV Putty Coarse



## Warning

H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H411-Toxic to aquatic life with long lasting effects.

P261-Avoid breathing dust. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection. P314-Get medical advice / attention if you feel unwell.

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate  
 exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate  
 Hexamethylene diacrylate  
 Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate  
 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid  
 Reaction mass of trimethylolpropane triacrylate and hexamethyleneimine

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Hexanoic acid, 6-[[[[[1,3,3-trimethyl-5-[[[[6-oxo-6-[2-[(1-oxo-2-propenyl)oxy]ethoxy]hexyl]oxy]carbonyl]amino]cyclohexyl]methyl]amino]carbonyl]oxy]-, 2-[(1-oxo-2-propenyl)oxy]ethylester</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	119107-13-0
<b>content %</b>	10-<25
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319
<b>Hexamethylene diacrylate</b>	
<b>Registration number (REACH)</b>	01-2119484737-22-XXXX
<b>Index</b>	607-109-00-8
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	235-921-9
<b>CAS</b>	13048-33-4
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411
<b>exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate</b>	

Page 3 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 04.10.2021 / 0003  
 Replacing version dated / version: 09.12.2020 / 0002  
 Valid from: 04.10.2021  
 PDF print date: 05.10.2021  
 UV Putty Fine  
 UV Putty Coarse

<b>Registration number (REACH)</b>	01-2119957862-25-XXXX
<b>Index</b>	607-133-00-9
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	227-561-6
<b>CAS</b>	5888-33-5
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

<b>Reaction mass of trimethylolpropane triacrylate and hexamethyleneimine</b>	
<b>Registration number (REACH)</b>	01-2120786563-43-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	946-043-7
<b>CAS</b>	2387352-64-7
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 3, H412

<b>4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid</b>	
<b>Registration number (REACH)</b>	01-2119490020-53-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	500-130-2
<b>CAS</b>	55818-57-0
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Sens. 1, H317 Aquatic Chronic 2, H411

<b>Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate</b>	
<b>Registration number (REACH)</b>	01-2119987994-10-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	282-810-6
<b>CAS</b>	84434-11-7
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Sens. 1B, H317 Aquatic Chronic 2, H411

<b>(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate</b>	
<b>Registration number (REACH)</b>	01-2119484613-34-XXXX
<b>Index</b>	607-249-00-X
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	256-032-2
<b>CAS</b>	42978-66-5
<b>content %</b>	0,5-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411
<b>Specific Concentration Limits and ATE</b>	STOT SE 3, H335: >=10 %

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Page 4 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 04.10.2021 / 0003  
Replacing version dated / version: 09.12.2020 / 0002  
Valid from: 04.10.2021  
PDF print date: 05.10.2021  
UV Putty Fine  
UV Putty Coarse

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

### **Inhalation**

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

### **Skin contact**

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### **Eye contact**

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### **Ingestion**

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.  
Give water to drink.  
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

eyes, reddened  
watering eyes  
reddening of the skin  
Dermatitis (skin inflammation)  
Allergic reaction

### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Water jet spray/foam/CO<sub>2</sub>/dry extinguisher

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Metal oxides  
Oxides of phosphorus  
Oxides of nitrogen  
Halogenated compounds  
Toxic gases

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Do not take any measures that are associated with personal risk or have not been sufficiently trained.  
Keep unprotected persons away.  
Ensure sufficient supply of air.  
Avoid contact with eyes or skin.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.10.2021 / 0003

Replacing version dated / version: 09.12.2020 / 0002

Valid from: 04.10.2021

PDF print date: 05.10.2021

UV Putty Fine

UV Putty Coarse

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Avoid build up of dust.

Fill the absorbed material into lockable containers.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Store in a dry place.

Store upright.

Recommended storage temperature:

20 - 25°C

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Silicon dioxide - amorphous		Content %:
WEL-TWA: 6 mg/m <sup>3</sup> (total inh. dust), 2,4 mg/m <sup>3</sup> (resp. dust)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		
Chemical Name	Talc		Content %:
WEL-TWA: 1 mg/m <sup>3</sup> (res. dust)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		
Chemical Name	China stone		Content %:
WEL-TWA: 2 mg/m <sup>3</sup> (res. dust)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		

Page 6 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 04.10.2021 / 0003  
 Replacing version dated / version: 09.12.2020 / 0002  
 Valid from: 04.10.2021  
 PDF print date: 05.10.2021  
 UV Putty Fine  
 UV Putty Coarse

Chemical Name	general dust limit	Content %:
WEL-TWA: 10 mg/m <sup>3</sup> (inhal. dust), 4 mg/m <sup>3</sup> (respir. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Hexamethylene diacrylate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,007	mg/l	
	Environment - marine		PNEC	0,001	mg/l	
	Environment - sewage treatment plant		PNEC	2,7	mg/l	
	Environment - sediment, freshwater		PNEC	0,493	mg/kg dw	
	Environment - sediment, marine		PNEC	0,049	mg/kg dw	
	Environment - soil		PNEC	0,094	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	2,1	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,66	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	7,2	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	24,5	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,77	mg/kg bw/d	

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,001	mg/l	
	Environment - marine		PNEC	0	mg/l	
	Environment - sediment, freshwater		PNEC	0,145	mg/kg dw	
	Environment - sediment, marine		PNEC	0,015	mg/kg dw	
	Environment - soil		PNEC	0,029	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,007	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,45	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,83	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,9	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,39	mg/kg bw/d	

Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1,01	µg/l	

	Environment - marine		PNEC	0,101	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10,1	µg/l	
	Environment - sediment, freshwater		PNEC	0,24	mg/kg dw	
	Environment - sediment, marine		PNEC	0,024	mg/kg dw	
	Environment - soil		PNEC	0,0475	mg/kg dw	

Silicon dioxide - amorphous						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period)  
 EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN ISO 374).  
 If applicable  
 Protective gloves made of butyl (EN ISO 374).  
 Protective Neoprene® / polychloroprene gloves (EN ISO 374).  
 Protective nitrile gloves (EN ISO 374).  
 Protective PVC gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 >= 0,5  
 Permeation time (penetration time) in minutes:  
 240 - 480  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

Page 8 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 04.10.2021 / 0003  
 Replacing version dated / version: 09.12.2020 / 0002  
 Valid from: 04.10.2021  
 PDF print date: 05.10.2021  
 UV Putty Fine  
 UV Putty Coarse

The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.  
 If air supply is not sufficient, wear protective breathing apparatus.  
 Filter A P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Solid
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Flash point:	n.a.
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
pH-value:	Not determined
Viscosity:	n.a.
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Vapour pressure:	Not determined
Density:	1,37 g/cm <sup>3</sup>
Vapour density (air = 1):	Not determined
Evaporation rate:	Not determined
Bulk density:	Not determined
Solubility(ies):	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Conductivity:	Not determined
Fat solubility / solvent:	Not determined
Solvents content:	Not determined
Surface tension:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Page 9 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 04.10.2021 / 0003  
 Replacing version dated / version: 09.12.2020 / 0002  
 Valid from: 04.10.2021  
 PDF print date: 05.10.2021  
 UV Putty Fine  
 UV Putty Coarse

The product has not been tested.

## 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

Hazardous polymerisation will not occur during storage and handling under normal conditions.

## 10.4 Conditions to avoid

Strong heat

## 10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

## 10.6 Hazardous decomposition products

No decomposition when used as directed.

# SECTION 11: Toxicological information

## 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

UV Putty Fine UV Putty Coarse						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hexamethylene diacrylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3650	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative

<b>exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	4350	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 487 (In Vitro Mammalian Cell Micronucleus Test)	Negative
Aspiration hazard:						No

<b>Reaction mass of trimethylolpropane triacrylate and hexamethyleneimine</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:					OECD 439 (In Vitro Skin Irritation - Reconstructed Human Epidermis Test Method)	Skin Irrit. 2
Serious eye damage/irritation:					OECD 492 (Reconstructed Human Cornea-like Epithelium ... Not Requir. C. + L. for Eye Irrit./Dam.)	Not irritant
Respiratory or skin sensitisation:					OECD 442D (In Vitro Skin Sensitisation: ARE-Nrf2 Luciferase Test Method)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

<b>Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 487 (In Vitro Mammalian Cell Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						itching

<b>(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>

Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit		Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:						Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	250	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Analogous conclusion

**Silicon dioxide - amorphous**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	IUCLID Chem. Data Sheet (ESIS)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	IUCLID Chem. Data Sheet (ESIS)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	>497	mg/kg bw/d			No indications of such an effect.
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,035	mg/l			Negative

**Talc**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

Page 12 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 04.10.2021 / 0003  
 Replacing version dated / version: 09.12.2020 / 0002  
 Valid from: 04.10.2021  
 PDF print date: 05.10.2021  
 UV Putty Fine  
 UV Putty Coarse

Carcinogenicity:						Negative
Reproductive toxicity:				Rat		Negative
Symptoms:						mucous membrane irritation

China stone						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant, Mechanical irritation possible.
Aspiration hazard:						No

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

UV Putty Fine UV Putty Coarse							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Hexamethylene diacrylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	30min	~270	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.2. Persistence and degradability:		28d	60-70	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Readily biodegradable
12.1. Toxicity to daphnia:	EC50	48h	2,7	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to fish:	LC50	96h	0,38	mg/l	Oryzias latipes	OECD 203 (Fish, Acute Toxicity Test)	

Page 13 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 04.10.2021 / 0003  
 Replacing version dated / version: 09.12.2020 / 0002  
 Valid from: 04.10.2021  
 PDF print date: 05.10.2021  
 UV Putty Fine  
 UV Putty Coarse

12.1. Toxicity to fish:	NOEC/NOEL		0,072	mg/l	Oryzias latipes	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,14	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1,09	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	

#### exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	0,704	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to algae:	EC50	72h	1,98	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	57	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,092	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	

#### Reaction mass of trimethylolpropane triacrylate and hexamethyleneimine

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		30d	62	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.1. Toxicity to daphnia:	EC50	48h	27	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	3,3	mg/l	Pseudokirchnerie lla subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,87	mg/l	Pseudokirchnerie lla subcapitata		
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.1. Toxicity to algae:	EC50	72h	1,01	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	

12.1. Toxicity to fish:	LC50	96h	1,89	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	<10	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.1. Toxicity to daphnia:	EC50	48h	2,26	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	48	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.1. Toxicity to fish:	LC50	96h	>4,5- <10	mg/l	Leuciscus idus	DIN 38412 T.15	
Toxicity to bacteria:	EC50	30min	>10000	mg/l	Pseudomonas putida		
Other information:	BOD/COD		>60	%			

**Silicon dioxide - amorphous**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to algae:	EC50	72h	>10000	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	30d	34223	mg/l	Daphnia magna		
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.1. Toxicity to algae:	IC50	72h	440	mg/l	Pseudokirchnerie lla subcapitata	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	60	mg/l	Pseudokirchnerie lla subcapitata	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

**Talc**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:			<0,1	%			
12.2. Persistence and degradability:							Not relevant for inorganic substances.

Page 15 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 04.10.2021 / 0003  
 Replacing version dated / version: 09.12.2020 / 0002  
 Valid from: 04.10.2021  
 PDF print date: 05.10.2021  
 UV Putty Fine  
 UV Putty Coarse

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	-------------------------------------

China stone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods., Mechanical precipitation possible.
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l			
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	LC50	48h	>1100	mg/l	Daphnia magna		References
12.1. Toxicity to algae:	IC50		>1000	mg/l			
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:							Not biodegradable
12.3. Bioaccumulative potential:							Not to be expected, Analogous conclusion
Water solubility:							Insoluble

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number:

3077

Transport by road/by rail (ADR/RID)

**14.2. UN proper shipping name:**

UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (HEXAMETHYLENE DIACRYLATE,EXO-1,7,7-TRIMETHYLBICYCLO[2.2.1]HEPT-2-YL ACRYLATE)

**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

**Classification code:**

M7

**LQ:**

5 kg

**14.5. Environmental hazards:**

environmentally hazardous

**Tunnel restriction code:**

-

**Transport by sea (IMDG-code)****14.2. UN proper shipping name:**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (HEXAMETHYLENE DIACRYLATE,EXO-1,7,7-TRIMETHYLBICYCLO[2.2.1]HEPT-2-YL ACRYLATE)

**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

**EmS:**

F-A, S-F

**Marine Pollutant:**

Yes

**14.5. Environmental hazards:**

environmentally hazardous

**Transport by air (IATA)****14.2. UN proper shipping name:**

Environmentally hazardous substance, solid, n.o.s. (HEXAMETHYLENE DIACRYLATE,EXO-1,7,7-TRIMETHYLBICYCLO[2.2.1]HEPT-2-YL ACRYLATE)

**14.3. Transport hazard class(es):**

9

**14.4. Packing group:**

III

**14.5. Environmental hazards:**

environmentally hazardous

**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Observe restrictions:**

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

**Directive 2010/75/EU (VOC):**

&lt; 0,3 %

Observe incident regulations.

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.10.2021 / 0003

Replacing version dated / version: 09.12.2020 / 0002

Valid from: 04.10.2021

PDF print date: 05.10.2021

UV Putty Fine

UV Putty Coarse

Revised sections:

2, 3, 5, 6, 8, 11, 12, 15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aquatic Acute — Hazardous to the aquatic environment - acute

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NLP No-longer-Polymer  
 NOEC, NOEL No Observed Effect Concentration/Level  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 PBT persistent, bioaccumulative and toxic  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 ppm parts per million  
 PVC Polyvinylchloride  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
 SVHC Substances of Very High Concern  
 Tel. Telephone  
 TOC Total organic carbon  
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
 VOC Volatile organic compounds  
 vPvB very persistent and very bioaccumulative  
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.