

# Safety Data Sheet

Product Name: Heavy-Bodied Seam Sealer Cartridge 200ml.

Product identifier: 106022

Revision Date: 06-09-2015

Replaces:



## 1. Identification

**Product Name:** Heavy-Bodied Seam Sealer Cartridge 200ml.  
**Product identifier:** 106022  
**Relevant identified uses of the substance or mixture and uses advised against:** Seam Sealer

**Chemical Manufacturer / Importer / Distributor:** ITW Evercoat  
a division of Illinois Tool Works Inc.  
6600 Cornell Road  
Cincinnati, OH 45242  
513-489-7600

**Emergency telephone number:** CHEMTREC: 1-800-424-9300  
CANUTEC: 1-613-996-6666

## 2. Hazard(s) identification

**Classification of the chemical in accordance with paragraph (d) of §1910.1200;**

**GHS Hazard Symbols:**



**GHS Classification:** Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2A  
Carcinogenicity Category 2

**GHS Signal Word:** Warning  
**GHS Hazard Statements:** Causes skin irritation.  
Causes serious eye irritation.  
Suspected of causing cancer.

**GHS Precautionary Statements:**  
**Safety Precautions:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wash thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Use personal protective equipment as required.  
**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

# Safety Data Sheet

**Product Name:** Heavy-Bodied Seam Sealer Cartridge 200ml.

**Product identifier:** 106022

**Revision Date:** 06-09-2015

**Replaces:**

if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing and wash before reuse.  
Store locked up.

**Storage:**

**Disposal:**

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

**Hazards not otherwise classified:**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

## 3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
2,4,6-Tris[(Dimethylamino) Methyl] Phenol	90-72-2	3 - 7
Rutile Titanium Dioxide	1317-80-2	1 - 5
Bis[(dimethylamino)methyl]phenol	71074-89-0	0.5 - 1.5

**the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required.**

## 4. First-aid measures

**Eye Contact:**

Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.

**Skin Contact:**

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing before reuse.

**Inhalation:**

Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen

# Safety Data Sheet

Product Name: Heavy-Bodied Seam Sealer Cartridge 200ml.

Product identifier: 106022

Revision Date: 06-09-2015

Replaces:

**Ingestion:** may be beneficial if administered by trained personnel, preferably on a doctor's advice. Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended.

**Immediate medical attention and special treatment needed,:** No additional first aid information available

## 5. Fire-fighting measures

**Suitable extinguishing media:** Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid. Regular foam Carbon dioxide Dry chemical

**Unsuitable extinguishing media:** No data available

**Fire and/or Explosion Hazards:** Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.

**Hazardous Combustion Products:** Carbon dioxide, Carbon monoxide, Hydrocarbons

**Special protective equipment and precautions for fire-fighters:** Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

**Methods and material for containment and cleaning up:** No special spill clean-up considerations. Collect and discard in regular trash. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid

# Safety Data Sheet

Product Name: Heavy-Bodied Seam Sealer Cartridge 200ml.

Product identifier: 106022

Revision Date: 06-09-2015

Replaces:

breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

## 7. Handling and storage

**Precautions for safe handling:** Mildly irritating material. Avoid unnecessary exposure. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

**Conditions for safe storage:** Store in a cool dry place. Isolate from incompatible materials. Store in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with incompatible materials.

**Materials to Avoid/Chemical Incompatibility::** Peroxides Strong acids Strong oxidizing agents Polymerization catalysts

## 8. Exposure controls/personal protection

### Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Rutile Titanium Dioxide	15 mg/m3	10 mg/m3	

**Appropriate engineering controls.:** No exposure limits exist for the constituents of this product. General room ventilation might be required to maintain operator comfort under normal conditions of use. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

**Eye Protection:** Wear safety glasses when handling this product. Splash proof chemical goggles are recommended to protect against the splash of product.

**Skin Protection:** Not normally considered a skin hazard. Where use can result in skin contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

# Safety Data Sheet

Product Name: Heavy-Bodied Seam Sealer Cartridge 200ml.

Product identifier: 106022

Revision Date: 06-09-2015

Replaces:

---

<b>Respiratory Protection:</b>	No respiratory protection required under normal conditions of use. Provide general room exhaust ventilation if symptoms of overexposure occur as explained Section III. A respirator is not normally required. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.
<b>Other Protective Equipment:</b>	Splash proof chemical goggles are recommended to protect against the splash of product. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots
<b>General Hygiene Conditions:</b>	All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

## 9. Physical and chemical properties

<b>Appearance (physical state):</b>	Paste
<b>Color:</b>	Beige
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	No data available
<b>pH:</b>	No data available
<b>Melting Point/Freezing Point (°C):</b>	No data available
<b>Initial Boiling Point and Boiling Range (°C):</b>	32
<b>Flash Point (°C):</b>	93.3
<b>Evaporation Rate:</b>	No data available
<b>Flammability (solid, gas):</b>	No data available
<b>Upper Flammable/Explosive Limit:</b>	No data available
<b>Lower Flammable/Explosive Limit:</b>	No data available
<b>Vapor Pressure:</b>	< 0.01 MMHG@70 F
<b>Vapor Density:</b>	Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
<b>Relative Density:</b>	Not determined
<b>Solubility(ies):</b>	Insoluble
<b>Partition coefficient: n-octanol/water:</b>	No data available
<b>Auto-ignition Temperature (°C):</b>	No data available
<b>Decomposition Temperature::</b>	No data available
<b>Viscosity:</b>	No data available
<b>VOC (as packaged-less exempts and water)</b>	0.004 or 0.47

# Safety Data Sheet

Product Name: Heavy-Bodied Seam Sealer Cartridge 200ml.

Product identifier: 106022

Revision Date: 06-09-2015

Replaces:

## 10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. Contamination.
Incompatible materials:	Peroxides Strong acids Strong oxidizing agents Polymerization catalysts
Hazardous decomposition products:	Carbon dioxide Carbon monoxide Styrene oxide Hydrocarbons

## 11. Toxicological information

**Likely routes of exposure (inhalation, ingestion, skin and eye contact):** Ingestion, Skin contact, Eye contact, Absorption

### Immediate (Acute) Health Effects by Route of Exposure:

<b>Inhalation Irritation:</b>	Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache and dizziness. Airborne overexposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema.
<b>Skin Contact:</b>	Can cause minor skin irritation, defatting, and dermatitis.
<b>Skin Absorption:</b>	Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Symptoms may include redness, burning, drying and cracking of skin, and skin burns
<b>Eye Contact:</b>	Can cause minor irritation, tearing and reddening. Contact may cause severe irritation, redness, swelling, tearing and blurred vision.
<b>Ingestion Irritation:</b>	Mildly irritating to mouth, throat, and stomach. Can cause abdominal discomfort. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
<b>Ingestion Toxicity:</b>	

### Long-Term (Chronic) Health Effects:

<b>Carcinogenicity:</b>	None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. This material may contain trace amounts of chemicals considered to be carcinogenic by OSHA, (1,3-Butadiene-IARC Group 2A).
<b>Reproductive and Developmental Toxicity:</b>	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
<b>Mutagenicity:</b>	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
<b>Inhalation:</b>	Upon prolonged and/or repeated exposure, can cause minor respiratory irritation,

# Safety Data Sheet

Product Name: Heavy-Bodied Seam Sealer Cartridge 200ml.

Product identifier: 106022

Revision Date: 06-09-2015

Replaces:

**Skin Contact:** dizziness, weakness, fatigue, nausea, and headache.  
Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

## Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available			

## 12. Ecological information

**Ecotoxicity (aquatic and terrestrial, where available):** This material is not expected to be harmful to the ecology. This material is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.

**Persistence and degradability:** No data available

**Mobility in soil:** No data available

**Other adverse effects (such as hazardous to the ozone layer):** No data available

## Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

## 13. Disposal considerations

**Description of waste residues:** Spent or discarded material is not expected to be a hazardous waste.

**Safe Handling of Waste:** Disposal must be in accordance with applicable Federal, State/Provincial and Local regulations.

**Waste treatment methods (including packaging):** Dispose of in a landfill. Disposal is not likely to be regulated.

## 14. Transport information

**UN proper shipping name:** The DOT Classification for shipping is dependent on quantity, type of packaging (a kit may include other components), or

# Safety Data Sheet

Product Name: Heavy-Bodied Seam Sealer Cartridge 200ml.

Product identifier: 106022

Revision Date: 06-09-2015

Replaces:

method of shipment.

## 15. Regulatory information

**TSCA Status:** All components in this product are on the TSCA Inventory.

### Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
No data available					

## 16. Other information, including date of preparation or last revision.

**Revision Date:** 06-09-2015

**Revision Number:** 3

**Disclaimer:** NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances