

1. IDENTIFICATION

Product identifier

Product Name EVERCOAT Z-GRIP OPTEX GLAZE

Other means of identification

Product Code 100567

Recommended use of the chemical and restrictions on use

Recommended Use Finishing Putty. For professional use only.

Uses advised against Uses other than recommended use.

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Evercoat
 A division of Illinois Tool Works Inc.
 6600 Cornell Road
 Cincinnati, OH 45242 USA
 513-489-7600

May Also Be Distributed by:

ITW Permatex Canada
 101-2360 Bristol Circle
 Oakville, ON Canada L6H 6M5
 Telephone: (800) 924-6994

24-hour emergency phone number

CHEMTREC: 1-800-424-9300
 INTERNATIONAL: 1-703-527-3887

E-mail address: Info@evercoat.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Signal word

Danger

Causes skin irritation
 Causes serious eye irritation
 May cause cancer
 Suspected of damaging fertility or the unborn child
 May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Flammable liquid and vapor

**Appearance** paste**Physical state** Liquid**Odor** Aromatic**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wear eye/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground and bond container and receiving equipment
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Use non-sparking tools
 Take action to prevent static discharges
 Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 IN CASE OF FIRE: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Styrene	100-42-5	10 - 30
Talc (hydrous magnesium silicate)	14807-96-6	10 - 30

Ground Limestone (Calcium Carbonate)	1317-65-3	10 - 30
Magnesite	546-93-0	3 - 7
Titanium Dioxide	13463-67-7	0.1 - 1
Crystalline Silica (Quartz)	14808-60-7	0.1 - 1
Benzenamine, N,N,4-Trimethyl	99-97-8	0.1 - 1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Use dry chemical, Foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Styrene 100-42-5	STEL: 20 ppm TWA: 10 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³
Talc (hydrous magnesium silicate) 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more;use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Ground Limestone (Calcium Carbonate) 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Magnesite 546-93-0	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium Dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Crystalline Silica (Quartz) 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

		(vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	
--	--	--	--

NIOSH IDLH *Immediately Dangerous to Life or Health*

Appropriate engineering controls

Engineering Controls Minimize exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings

Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
- Respiratory protection** Use NIOSH-approved half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates.

General Hygiene Considerations Do not eat, drink or smoke when using this product. Take off all contaminated clothing and wash it before reuse. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	paste
Odor	Aromatic
Color	pink
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	145 °C / 293 °F	
Flash point	31.5 °C / 88.7 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	Insoluble in water	
Solubility(ies)	Acetone	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Hyphen	No information available	
Kinematic viscosity	0.0148 m ² /s	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information	
Softening point	No information available
Molecular weight	No information available
Applied	0.65 lbs/gal

Packaged	1.78 lbs/gal
Density	7.9 lbs/gal
Bulk density	No information available
SADT (self-accelerating decomposition temperature)	No information available

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 11.7 mg/L (Rat) 4 h
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
Benzenamine, N,N,4-Trimethyl 99-97-8	= 1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 1400 mg/m ³ (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Styrene 100-42-5	A3	Group 2A	Reasonably Anticipated	X
Talc (hydrous magnesium silicate) 14807-96-6	-	Group 3	-	X
Titanium Dioxide 13463-67-7	-	Group 2B	-	X

Crystalline Silica (Quartz) 14808-60-7	A2	Group 1	Known	X
Benzenamine, N,N,4-Trimethyl 99-97-8	-	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)
 A2 - Suspected Human Carcinogen
 IARC (International Agency for Research on Cancer)
 Group 2B - Possibly Carcinogenic to Humans
 Group 3 - Not classifiable as a human carcinogen
 Group 1 - Carcinogenic to Humans
 Group 2A - Probably Carcinogenic to Humans
 NTP (National Toxicology Program)
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 Known - Known Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Chronic toxicity May cause adverse liver effects. Contains a known or suspected reproductive toxin.
Target organ effects Central nervous system, Central Vascular System (CVS), Eyes, Liver, Reproductive system, Respiratory system, Skin, Lungs.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 40984 mg/kg
ATEmix (dermal) 11804 mg/kg
ATEmix (inhalation-dust/mist) 205.3 mg/l
ATEmix (inhalation-vapor) 42.4 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical name	Partition coefficient
Styrene 100-42-5	2.95
Benzenamine, N,N,4-Trimethyl 99-97-8	2.81

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Styrene 100-42-5	Toxic Ignitable

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN/ID No UN3269
 Proper shipping name Polyester Resin Kit
 Transport hazard class(es) 3
 Packing Group III

IATA

UN number or ID number UN3269
 Proper shipping name Polyester Resin Kit
 Transport hazard class(es) 3
 Packing group III

IMDG

UN number or ID number UN3269
 Proper shipping name Polyester Resin Kit
 Transport hazard class(es) 3
 Packing Group III

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Not determined
 ENCS Complies
 IECS Complies
 KECL Complies
 PICCS Complies
 AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECS - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Styrene 100-42-5	Carcinogen
Titanium Dioxide 13463-67-7	Carcinogen
Crystalline Silica (Quartz) 14808-60-7	Carcinogen
Benzenamine, N,N,4-Trimethyl 99-97-8	Carcinogen
N-Methyl-2-pyrrolidone 872-50-4	Developmental
Methanol 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Styrene 100-42-5	X	X	X
Talc (hydrous magnesium silicate) 14807-96-6	X	X	X
Ground Limestone (Calcium Carbonate) 1317-65-3	X	X	X
Magnesite 546-93-0	X	X	-
Synthetic Amorphous Silica 112926-00-8	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Crystalline Silica (Quartz) 14808-60-7	X	X	X
Isopentane 78-78-4	X	X	X
N-Methyl-2-pyrrolidone 872-50-4	X	X	X
Paraffin Wax 8002-74-2	X	X	X
Methanol 67-56-1	X	X	X

1,4-NAPHTHOQUINONE 130-15-4	X	X	X
--------------------------------	---	---	---

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials, B3 - Combustible liquid

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	-
HMIS	Health hazards 3*	Flammability 2	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
 HMIS (Hazardous Material Information System)

Revision Date 23-Jun-2023

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet