



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

1 Identification

- **Product identifier**
- **Trade name:** HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT
- **Article number:** 77750
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
HIGH TECK PRODUCTS
PO BOX 24631
WEST PALM BEACH, FLORIDA 33416
USA
877-900-8325
info@highteckproducts.com
- **Information department:** Product safety department
- **Emergency telephone number:** 800 424-9300 (Chemtrec)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.

Carcinogenicity 1A H350 May cause cancer.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 1)

Aquatic Acute 2

H401 Toxic to aquatic life.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Talc ($Mg_3H_2(SiO_3)_4$)

Stoddard solvent

Carbon black

ethylbenzene

2-butanone oxime

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO₂, powder or water spray to extinguish.

Collect spillage.

Store in a well-ventilated place. Keep cool.

Store locked up.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 2)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 3
Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	25-50%
107-87-9	pentan-2-one	10-25%
123-86-4	n-butyl acetate	2.5-10%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
67-64-1	acetone	2.5-10%
79-20-9	methyl acetate	2.5-10%
110-43-0	heptan-2-one	2.5-10%
7779-90-0	trizinc bis(orthophosphate)	≤2.5%
1333-86-4	Carbon black	≤2.5%
100-41-4	ethylbenzene	≤2.5%
8052-41-3	Stoddard solvent	≤2.5%
96-29-7	2-butanone oxime	≤2.5%
64-17-5	ethanol	≤2.5%

4 First-aid measures

- **Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	xylene	130 ppm
107-87-9	pentan-2-one	150 ppm
123-86-4	n-butyl acetate	5 ppm
67-64-1	acetone	200 ppm
79-20-9	methyl acetate	250 ppm
110-43-0	heptan-2-one	150 ppm
7779-90-0	trizinc bis(orthophosphate)	12 mg/m ³
1333-86-4	Carbon black	9 mg/m ³
100-41-4	ethylbenzene	33 ppm
8052-41-3	Stoddard solvent	1700 mg/m ³
96-29-7	2-butanone oxime	8.0 mg/m ³
64-17-5	ethanol	1,800 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
67-56-1	methanol	530 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 4)

112-34-5	2-(2-butoxyethoxy)ethanol	200 mg/m ³
149-57-5	2-ethylhexanoic acid	15 mg/m ³
67-63-0	propan-2-ol	400 ppm

PAC-2:

1330-20-7	xylene	920* ppm
107-87-9	pentan-2-one	830 ppm
123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
79-20-9	methyl acetate	1,700 ppm
110-43-0	heptan-2-one	670 ppm
7779-90-0	trizinc bis(orthophosphate)	36 mg/m ³
1333-86-4	Carbon black	290 mg/m ³
100-41-4	ethylbenzene	1100 ppm
8052-41-3	Stoddard solvent	1800 mg/m ³
96-29-7	2-butanone oxime	150 mg/m ³
64-17-5	ethanol	3300* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
67-56-1	methanol	2100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	220 mg/m ³
149-57-5	2-ethylhexanoic acid	99 mg/m ³
67-63-0	propan-2-ol	2000* ppm

PAC-3:

1330-20-7	xylene	2500* ppm
107-87-9	pentan-2-one	5000* ppm
123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm
79-20-9	methyl acetate	10000* ppm
110-43-0	heptan-2-one	4000* ppm
7779-90-0	trizinc bis(orthophosphate)	220 mg/m ³
1333-86-4	Carbon black	1750 mg/m ³
100-41-4	ethylbenzene	1800 ppm
8052-41-3	Stoddard solvent	20000 mg/m ³
96-29-7	2-butanone oxime	880 mg/m ³
64-17-5	ethanol	15000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
67-56-1	methanol	7200 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	1300 mg/m ³
149-57-5	2-ethylhexanoic acid	590 mg/m ³
67-63-0	propan-2-ol	12000** ppm

USA

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 5)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

107-87-9 pentan-2-one

PEL	Long-term value: 700 mg/m ³ , 200 ppm
REL	Long-term value: 530 mg/m ³ , 150 ppm
TLV	Short-term value: 529 mg/m ³ , 150 ppm

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
-----	--

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 6)

REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm A4, BEI

79-20-9 methyl acetate

PEL	Long-term value: 610 mg/m ³ , 200 ppm
REL	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm
TLV	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm

110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 50 ppm

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction, A3

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm

96-29-7 2-butanone oxime

WEEL	Long-term value: 10 ppm DSEN
------	---------------------------------

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm A3

Ingredients with biological limit values:**1330-20-7 xylene**

BEI	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 7)

67-64-1 acetone

BEI 25 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 8)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Black
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)

· **Flash point:** <-18 °C (<-0.4 °F)

· **Flammability:** Highly flammable.

· **Auto igniting:** 370 °C (698 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1.1 Vol %
Upper:	8.2 Vol %

· **Vapor pressure at 20 °C (68 °F):** 16 hPa (12 mm Hg)

· **Vapor pressure at 50 °C (122 °F):** 92 hPa (69 mm Hg)

· **Density at 20 °C (68 °F):** 1.1428 g/cm³ (9.5367 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· Solvent content:

Organic solvents:	86.8 %
Water:	0.1 %
VOC content:	75.94 %
	535.6 g/l / 4.47 lb/gal

Solids content: 50.0 %

· **Other information** No further relevant information available.

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 9)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

107-87-9 pentan-2-one

Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	6,500 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2A
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
136-52-7	cobalt(II) 2-ethylhexanoate	2A
67-63-0	propan-2-ol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT


(Contd. of page 10)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|-------------------------|
| UN-Number | UN1263 |
| DOT, IMDG, IATA | |
| UN proper shipping name | Paint |
| DOT | PAINT, MARINE POLLUTANT |
| IMDG | PAINT |
| IATA | |
| Transport hazard class(es) | |
| DOT | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 11)

· **IMDG**

· **Class** 3 Flammable liquids
 · **Label** 3

· **IATA**

· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**
 · **DOT, IMDG, IATA** II

· **Environmental hazards:**
 · **Marine pollutant:** Symbol (fish and tree)

· **Special precautions for user** Warning: Flammable liquids
 · **Hazard identification number (Kemler code):** 33
 · **EMS Number:** F-E, S-E
 · **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **IMDG**

· **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

7779-90-0 trizinc bis(orthophosphate)

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 12)

100-41-4	ethylbenzene
136-52-7	cobalt(II) 2-ethylhexanoate
67-56-1	methanol
112-34-5	2-(2-butoxyethoxy)ethanol
67-63-0	propan-2-ol

· **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
107-87-9	pentan-2-one	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	ACTIVE
67-64-1	acetone	ACTIVE
79-20-9	methyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
7779-90-0	trizinc bis(orthophosphate)	ACTIVE
1333-86-4	Carbon black	ACTIVE
100-41-4	ethylbenzene	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
22464-99-9	22464-99-9	ACTIVE
96-29-7	2-butanone oxime	ACTIVE
64-17-5	ethanol	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
64742-48-9	Naphtha (petroleum), hydrotreated heavy	ACTIVE
136-52-7	cobalt(II) 2-ethylhexanoate	ACTIVE
67-56-1	methanol	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
149-57-5	2-ethylhexanoic acid	ACTIVE
67-63-0	propan-2-ol	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
136-52-7	cobalt(II) 2-ethylhexanoate
67-56-1	methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4	Carbon black
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
67-56-1	methanol

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 13)

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
67-64-1	acetone	I
7779-90-0	trizinc bis(orthophosphate)	D, I, II
100-41-4	ethylbenzene	D

- **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
67-64-1	acetone	A4
1333-86-4	Carbon black	A4
100-41-4	ethylbenzene	A3
64-17-5	ethanol	A3
67-63-0	propan-2-ol	A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Talc (Mg₃H₂(SiO₃)₄)

Stoddard solvent

Carbon black

ethylbenzene

2-butanone oxime

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 15)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77750-1(4) 1K BLACK SEALER NR/SC COMPLIANT

(Contd. of page 14)

- Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.
 Avoid release to the environment.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Collect spillage.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **National regulations:**
 - **Information about limitation of use:**
 Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
 - **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Contact:**
- **Date of preparation / last revision** 07/15/2025 / -
- **Abbreviations and acronyms:**
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 2: Flammable liquids – Category 2
 Skin Irritation 2: Skin corrosion/irritation – Category 2
 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
 Sensitization - Skin 1: Skin sensitisation – Category 1
 Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B
 Carcinogenicity 1A: Carcinogenicity – Category 1A
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2