



Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

1 Identification

- **Product identifier**
- **Trade name:** HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT
- **Article number:** 77752
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
HIGH TECK PRODUCTS
PO BOX 24631
WEST PALM BEACH, FLORIDA 33416
USA
877-900-8325
info@highteckproducts.com
- **Information department:** Product safety department
- **Emergency telephone number:** 800 424-9300 (Chemtrec)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.
Carcinogenicity 1A H350 May cause cancer.



GHS07

Skin Irritation 2 H315 Causes skin irritation.
 Eye Irritation 2A H319 Causes serious eye irritation.
 Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Talc ($Mg_3H_2(SiO_3)_4$)

Stoddard solvent

titanium dioxide

ethylbenzene

2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	25-50%
107-87-9	pentan-2-one	10-25%
123-86-4	n-butyl acetate	2.5-10%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
67-64-1	acetone	2.5-10%
79-20-9	methyl acetate	2.5-10%
110-43-0	heptan-2-one	2.5-10%
13463-67-7	titanium dioxide	2.5-10%
7779-90-0	trizinc bis(orthophosphate)	≤2.5%
100-41-4	ethylbenzene	≤2.5%
1333-86-4	Carbon black	≤2.5%
8052-41-3	Stoddard solvent	≤2.5%
96-29-7	2-butanone oxime	≤2.5%
64-17-5	ethanol	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	xylene	130 ppm
107-87-9	pentan-2-one	150 ppm
123-86-4	n-butyl acetate	5 ppm
67-64-1	acetone	200 ppm
79-20-9	methyl acetate	250 ppm
110-43-0	heptan-2-one	150 ppm
13463-67-7	titanium dioxide	30 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	12 mg/m ³
100-41-4	ethylbenzene	33 ppm
1333-86-4	Carbon black	9 mg/m ³
8052-41-3	Stoddard solvent	1700 mg/m ³
96-29-7	2-butanone oxime	8.0 mg/m ³
64-17-5	ethanol	1,800 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
67-56-1	methanol	530 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 mg/m ³

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 4)

7664-38-2	phosphoric acid	3 mg/m ³
149-57-5	2-ethylhexanoic acid	15 mg/m ³
108-38-3	m-xylene	130 ppm
122-99-6	2-phenoxyethanol	1.5 ppm
7440-50-8	copper	3 mg/m ³
67-63-0	propan-2-ol	400 ppm
556-67-2	octamethylcyclotetrasiloxane	360 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm

PAC-2:

1330-20-7	xylene	920* ppm
107-87-9	pentan-2-one	830 ppm
123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
79-20-9	methyl acetate	1,700 ppm
110-43-0	heptan-2-one	670 ppm
13463-67-7	titanium dioxide	330 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	36 mg/m ³
100-41-4	ethylbenzene	1100 ppm
1333-86-4	Carbon black	290 mg/m ³
8052-41-3	Stoddard solvent	1800 mg/m ³
96-29-7	2-butanone oxime	150 mg/m ³
64-17-5	ethanol	3300* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
67-56-1	methanol	2100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	220 mg/m ³
7664-38-2	phosphoric acid	30 mg/m ³
149-57-5	2-ethylhexanoic acid	99 mg/m ³
108-38-3	m-xylene	920 ppm
122-99-6	2-phenoxyethanol	16 ppm
7440-50-8	copper	33 mg/m ³
67-63-0	propan-2-ol	2000* ppm
556-67-2	octamethylcyclotetrasiloxane	530 mg/m ³
14808-60-7	Quartz (SiO ₂)	8.3 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm

PAC-3:

1330-20-7	xylene	2500* ppm
107-87-9	pentan-2-one	5000* ppm
123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 5)

79-20-9	methyl acetate	10000* ppm
110-43-0	heptan-2-one	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	220 mg/m ³
100-41-4	ethylbenzene	1800 ppm
1333-86-4	Carbon black	1750 mg/m ³
8052-41-3	Stoddard solvent	20000 mg/m ³
96-29-7	2-butanone oxime	880 mg/m ³
64-17-5	ethanol	15000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
67-56-1	methanol	7200 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	1300 mg/m ³
7664-38-2	phosphoric acid	150 mg/m ³
149-57-5	2-ethylhexanoic acid	590 mg/m ³
108-38-3	m-xylene	2500* ppm
122-99-6	2-phenoxyethanol	97 ppm
7440-50-8	copper	200 mg/m ³
67-63-0	propan-2-ol	12000** ppm
556-67-2	octamethylcyclotetrasiloxane	1600 mg/m ³
14808-60-7	Quartz (SiO ₂)	50 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

USA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 6)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, A4

107-87-9 pentan-2-one

PEL Long-term value: 700 mg/m³, 200 ppm

REL Long-term value: 530 mg/m³, 150 ppm

TLV Short-term value: 529 mg/m³, 150 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
A4, BEI

79-20-9 methyl acetate

PEL Long-term value: 610 mg/m³, 200 ppm

REL Short-term value: 760 mg/m³, 250 ppm
Long-term value: 610 mg/m³, 200 ppm

TLV Short-term value: 757 mg/m³, 250 ppm
Long-term value: 606 mg/m³, 200 ppm

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
OTO, BEI, A3

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 7)

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction, A3

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm

96-29-7 2-butanone oxime

WEEL	Long-term value: 10 ppm DSEN
------	---------------------------------

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm A3

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

67-64-1 acetone

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

100-41-4 ethylbenzene

BEI	0.15 g/g creatinine Medium: urine Time: end of shift Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 8)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Liquid
· Color:	Grey
· Odor:	Characteristic
· Odor threshold:	Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)

- **Flash point:** <-18 °C (<-0.4 °F)

- **Flammability:** Highly flammable.

- **Auto igniting:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

· Lower:	1.1 Vol %
-----------------	-----------

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 9)

Upper:	8.2 Vol %
· Vapor pressure at 20 °C (68 °F):	16 hPa (12 mm Hg)
· Vapor pressure at 50 °C (122 °F):	92 hPa (69 mm Hg)
· Density at 20 °C (68 °F):	1.2068 g/cm ³ (10.0707 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	83.1 %
Water:	0.1 %
VOC content:	72.94 %
	536.5 g/l / 4.48 lb/gal
· Solids content:	52.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

107-87-9 pentan-2-one

Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	6,500 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 10)

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2A
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
1333-86-4	Carbon black	2B
64-17-5	ethanol	1
136-52-7	cobalt(II) 2-ethylhexanoate	2A
95-47-6	o-xylene	3
106-42-3	p-xylene	3
108-38-3	m-xylene	3
67-63-0	propan-2-ol	3
14808-60-7	Quartz (SiO ₂)	1

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025



Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 11)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | Paint
PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | II |
| <ul style="list-style-type: none"> · Environmental hazards: | Not applicable. |
| <ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category | Warning: Flammable liquids
33
F-E, S-E
B |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 12)

- | | |
|--|---|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1263 PAINT, 3, II</p> |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
7779-90-0	trizinc bis(orthophosphate)
100-41-4	ethylbenzene
136-52-7	cobalt(II) 2-ethylhexanoate
67-56-1	methanol
112-34-5	2-(2-butoxyethoxy)ethanol
7664-38-2	phosphoric acid
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
122-99-6	2-phenoxyethanol
7440-50-8	copper
67-63-0	propan-2-ol

- **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
107-87-9	pentan-2-one	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	ACTIVE
67-64-1	acetone	ACTIVE
79-20-9	methyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
7779-90-0	trizinc bis(orthophosphate)	ACTIVE
100-41-4	ethylbenzene	ACTIVE
1333-86-4	Carbon black	ACTIVE
51274-00-1	ALPHA-IRON(III) OXIDE	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
22464-99-9	22464-99-9	ACTIVE
96-29-7	2-butanone oxime	ACTIVE

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 13)

64-17-5	ethanol	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
64742-48-9	Naphtha (petroleum), hydrotreated heavy	ACTIVE
136-52-7	cobalt(II) 2-ethylhexanoate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
67-56-1	methanol	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
149-57-5	2-ethylhexanoic acid	ACTIVE
95-47-6	o-xylene	ACTIVE
106-42-3	p-xylene	ACTIVE
108-38-3	m-xylene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
136-52-7	cobalt(II) 2-ethylhexanoate
67-56-1	methanol
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
67-56-1	methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
67-64-1	acetone	I
7779-90-0	trizinc bis(orthophosphate)	D, I, II
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 14)

106-42-3	<i>p</i> -xylene	I
108-38-3	<i>m</i> -xylene	I
7440-50-8	copper	D

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
100-41-4	ethylbenzene	A3
1333-86-4	Carbon black	A4
64-17-5	ethanol	A3
95-47-6	<i>o</i> -xylene	A4
106-42-3	<i>p</i> -xylene	A4
108-38-3	<i>m</i> -xylene	A4
67-63-0	propan-2-ol	A4
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Talc (Mg₃H₂(SiO₃)₄)

Stoddard solvent

titanium dioxide

ethylbenzene

2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

(Contd. on page 16)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 15)

*Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.
 Avoid release to the environment.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO2, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **National regulations:**
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Contact:**
- **Date of preparation / last revision** 07/15/2025 / -
- **Abbreviations and acronyms:**
*IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEL: Biological Exposure Limit
 Flammable Liquids 2: Flammable liquids – Category 2
 Skin Irritation 2: Skin corrosion/irritation – Category 2
 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A*

(Contd. on page 17)

USA

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2025

Reviewed on 07/15/2025

Trade name: HIT_77752-1(4) 1K GRAY SEALER NR/SC COMPLIANT

(Contd. of page 16)

*Sensitization - Skin 1: Skin sensitisation – Category 1**Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B**Carcinogenicity 1A: Carcinogenicity – Category 1A**Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

USA