



HIGH TECK TECHNICAL DATA SHEETS

URETHANE REDUCER

**W7710-1, W7710-5,
W7720-1, W7720-5,
W7730-1, W7730-5**

Urethane Grade Reducer that can be used to dilute all water-free urethane based paints and primers. Allows maximum pot life and improves flow and leveling.

PRODUCT	DESCRIPTION	SIZE
W7710-1	Slow Urethane Reducer	U.S. Gallon (3.78 L)
W7710-5	Slow Urethane Reducer	5 U.S. Gallon (18.9 L)
W7720-1	Medium Urethane Reducer	U.S. Gallon (3.78 L)
W7720-5	Medium Urethane Reducer	5 U.S. Gallon (18.9 L)
W7730-1	Fast Urethane Reducer	U.S. Gallon (3.78 L)
W7740-5	Fast Urethane Reducer	5 U.S. Gallon (18.9 L)



READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials. Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

FEATURES:

- Alcohol free
- Better flow-out
- Universal with virtually all water free urethane based paints, primers, basecoats, and clearcoats that require a urethane grade reducer.
- Urethane grade and urethane quality - contains no alcohol or moisture.
- 50 State Compliant Product are available.

DIRECTIONS:

Slowly add and mix Urethane Grade Reducer to basecoats, paints, primers until desired consistency and viscosity is obtained.

Note: follow paint or primer manufacturer's direction for reduction ratios. Read all warnings and directions for safe usage and proper application. It is important to verify the compatibility of this product with your paint system in a small sample. When using solvents for cleanup, use proper precautionary measure for handling and follow all proper local disposal procedures and regulations.



HIGH TECK TECHNICAL DATA SHEETS

URETHANE REDUCER

**W7710-1, W7710-5,
W7720-1, W7720-5,
W7730-1, W7730-5**

TECHNICAL DATA:

	W7710-1 / W7710-5	W7720-1 / W7720-5	W7730-1 / W7730-5
Physical State:	Liquid		
Color:	Clear, colorless		
Odor:	Solvent odor	Solvent odor	Solvent odor
Solubility:	No data	No data	Negligible
Flashpoint:	-9°C / 15.8 °F (estimated)	-9°C / 15.8 °F (estimated)	-18°C / 0°F (estimate; lowest flash point ingredient).
Auto ignition temperature	320°C / 608°F	320°C / 608°F	320°C / 608°F
VOC	7.02 lbs/g - 841.2 g/l	7.02 lbs/g - 841.2 g/l	3.71 lbs/g - 444 g/l

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available from High Teck. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that High Teck believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond High Teck's control and uniquely within user's knowledge and control can affect the use and performance of a High Teck product in a particular application. Given the variety of factors that can affect the use and performance of a High Teck product, user is solely responsible for evaluating the High Teck product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

High Teck makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, High Teck's total liability shall not exceed the purchase price of the product. At its option, High Teck may instead replace or repair the product. In no event shall High Teck be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that High Teck believes are reliable, but the accuracy or completeness of such information is not guaranteed.