

# **SAFETY DATA SHEET**

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME: ACRYL-GLO Acrylic Enamel**

**MANUFACTURER:**

COVENTRY COATINGS CORP.  
 dba Kirker Automotive Finishes  
 89 Taft Ave.  
 Newburgh, NY 12550  
 USA: 1-800-307-7951 or (845) 562-5666

**EMERGENCY CONTACT FOR  
 SPILL, FIRE, EXPLOSION:  
 CHEM-TREC 1-800-424-9300**

**PRODUCT CODES:**

KS-10384	Omaha Orange	KS-41087	Blue Metallic	KS-61260	Gray Metallic
KS-10401	Hwy Cat Yellow	KS-41089	Bright Aqua Pearl	KS-61268	Med Charcoal Gray Met
KS-10637	School Bus Yellow	KS-41090	Ultra Blue Pearl	KS-70330	Super Jet Black
KS-11058	New Cat Yellow	KS-41092	Royal Blue Pearl	KS-70356	Black Cherry Pearl
KS-11105	Viper Yellow	KS-51380	Dark Plum Met	KS-70357	Black Starburst
KS-11109	Mack Orange	KS-51400	Candy Apple Red	KS-70358	Black Sapphire Metallic
KS-11110	Mack Yellow	KS-51416	Mack Red	KS-81030	Pure White
KS-11115	Mocha Frost Pearl Met	KS-51429	Flame Red	KS-81496	Fleet White
KS-31252	Dark Jade Metallic	KS-51436	Raspberry Red Pearl Met	KS-81500	Wimbledon White
KS-31263	Mack Green	KS-51438	Dark Garnet Red Met	KS-81508	Mack White
KS-31267	Bright Calypso Green Met	KS-51439	Viper Red	KS-81522	White (GM code 40)
KS-41075	Bright Blue Metallic	KS-61231	Silver Metallic	KS-81525	Bright White
KS-41077	Mack Blue	KS-61235	Platinum Silver Met	KS-81535	Winter White
KS-41085	Lt Sapphire Blue Met	KS-61240	Oxford Gray		

## **SECTION 2: HAZARD IDENTIFICATION**

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

**Classification:**

FLAMMABLE LIQUIDS:	Category 2
ACUTE TOXICITY Inhalation:	Category 4
ACUTE TOXICITY Oral:	Category 4
ACUTE TOXICITY Dermal:	Category 4
ASPIRATION HAZARD:	Category 1
CARCINOGENICITY:	Category 2
SKIN IRRITATION:	Category 2
EYE IRRITATION:	Category 2A
SPECIFIC TARGET ORGAN TOXICITY:	
SINGLE EXPOSURE:	Category 3 (Respiratory, Central Nervous System)
REPEATED EXPOSURE:	Category 2 (Liver, Kidney, Central Nervous System)
	Percentage of mixture consisting of ingredients of unknown toxicity: 20%

**GHS Label Elements:**

**PICTOGRAMS**



**SIGNAL WORD:**

**Danger**

**Hazard Statements:**

Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin, causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation, drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

**Precautionary Statements:**

**Prevention:**

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Use personal protective equipment as required, (see Section 8). Wear protective gloves, protective clothing, eye and face protection. Wear an appropriate, properly fitted fresh air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors and spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated in Section 8. If medical advice is needed, have product container or label at hand. Avoid release to the environment. Keep out of reach of children and pets at all times.

<b>Response:</b>	Get Medical attention if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water or shower. If skin irritation or rash occurs: Get medical attention. Immediately call a POISON CENTER or physician if you feel unwell. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction, do not use water, see Section 5.
<b>Storage:</b>	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
<b>Disposal:</b>	Dispose of contents and container in accordance with all local, regional, national and international regulations.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Ingredient Name</b>	<b>CAS Number</b>	<b>% by Weight</b>
*ALKYD IN XYLENE	Mixture	40 – 50 %
*XYLENE	1330-20-7	10 – 30 %
TITANIUM DIOXIDE	13463-67-7	15 – 20 %
*HIGH FLASH NAPHTHA	64742-95-6	1 – 5 %
*BUTYL CELLOSOLVE	111-76-2	1 – 5 %
ISOPROPYL ALCOHOL	67-63-0	.05 – 1 %

\* Indicates chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372

### **SECTION 4: FIRST AID MEASURES**

<b>Eyes:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, check for and remove contact lenses. Seek immediate medical attention.
<b>Skin:</b>	Remove contaminated clothing. Immediately flush exposed area with large amounts of water. If symptoms persist, seek medical attention. Wash clothing separately and clean shoes before reuse.
<b>Ingestion:</b>	Seek immediate medical attention, contact physician or poison control center. Do NOT induce vomiting unless directed to do so by medical professional. Never give anything by mouth to an unconscious person.
<b>Inhalation:</b>	Seek immediate medical attention. Remove from exposure to fresh air. If not breathing or if breathing is irregular, provide artificial respiration or oxygen by trained personnel; rescuers should put on appropriate protective gear.

#### **MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:**

Vapor and spray mist harmful. May be harmful or fatal if swallowed, aspiration hazard. Exposure may cause lung damage, allergic reaction and respiratory reaction. May cause eye, skin, nose, throat and respiratory irritation. May affect the central nervous system causing dizziness, headache, or nausea. May cause skin dryness or cracking. Sanding dust may be harmful if inhaled, do not breath dust, use personal protective equipment.

<b>Effects:</b>	Repeated and prolonged overexposure to solvents may lead to permanent brain and nervous system damage causing dizziness, headache, or nausea and may cause adverse liver and kidney effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. Individuals with chronic respiratory problems should neither use this product nor be exposed to its vapors or spray mist.
<b>Notes to Physician:</b>	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Symptoms of poisoning may appear several hours after exposure.

### **SECTION 5: FIRE FIGHTING MEASURES**

#### **Suitable Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Alcohol-resistant Foam. Do not use water, material will float and may ignite on surface of water.

#### **Fire Fighting Procedures:**

Fight as volatile liquid fire Wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Eliminate all sources of ignition. Evacuate unnecessary personnel. Use water spray to cool containers with caution, avoid spreading burning liquid. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

#### **Unusual Fire and Explosion Hazard:**

Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Vapors/dust may cause flash fire or explosion. This material may be ignited by heat, sparks, flame or static electricity. Closed containers may explode when exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **Environmental Precautions:**

Avoid runoff and contact with soil, drains, sewers and waterways. Contact appropriate authority if spill is in excess of reportable quantity.

#### **Personal Precautions:**

Eliminate all ignition sources. No smoking, do not use flares. Contact emergency personnel. Evacuate the spill area and keep unnecessary, unprotected personnel away. Do not breathe vapors, use suitable personal protective equipment. Do not touch or walk through spilled material. Prevent additional discharge of material if able to do so safely. Ventilate spill area.

#### **Method of Cleaning Up:**

For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material, or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal using non-sparking tools.

Dispose of spilled material and contaminated absorbent material in compliance with local and national regulations, use a licensed waste disposal contractor, refer to Section 13.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling:**

Use only in a well ventilated area, with appropriate personal protective equipment, (see section 8). Do not eat, drink or smoke when handling this material. Wash hands and face before eating, drinking or smoking. Do not breathe vapor, fumes or mist. Do not get in eyes, or on skin, or clothing.

Always open containers slowly to allow any excess pressure to vent. Containers should be grounded when pouring. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-proof tools and explosion proof equipment.

This material is part of a multiple component system, read the Safety Data Sheet(s) for all components before mixing, as the mixture will have the hazards of all of its parts. Empty containers retain product residue and can be hazardous. Do not reuse container.

### **Conditions for Safe Storage, Including Incompatibilities:**

Store in accordance with local regulations. Store locked up. Keep container closed when not in use. Isolate from heat, flame, sparks, pilot lights, smoking materials and other sources of ignition. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated, explosion proof area. Protect from direct sunlight.  
KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Ingredient Name</b>	<b>CAS</b>	<b>Exposure Limits</b>
ALKYD IN XYLENE	Mixture	Data not available
BUTYL CELLOSOLVE	111-76-2	ACGIH TWA 20 ppm OSHA PEL TWA 50 ppm
HIGH FLASH NAPHTHA	64742-95-6	Data not available
ISOPROPYL ALCOHOL	67-63-0	ACGIH TWA 200 ppm OSHA PEL TWA 400 ppm
TITANIUM DIOXIDE	13463-67-7	ACGIH TLV 10mg/m <sup>3</sup> OSHA PEL TWA 15mg/m <sup>3</sup> dust
XYLENE	1330-20-7	ACGIH TWA 100ppm OSHA PEL TWA 100ppm

**Engineering Controls:** Provide explosion proof exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

### **Personal Protective Equipment**

**Eyes and Face:** Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

**Skin:** Wear impervious gloves to prevent contact with the skin. Where contact is likely, wear chemical resistant gloves, a chemical suit, long sleeves, rubber boots, and chemical safety goggles plus a face shield.

**Respiratory:** Wear an appropriate, properly fitted fresh-air supplied respirator, (NIOSH-approved TC-19C or equivalent), during and after application, until all organic vapors and spray mists are exhausted or any time airborne contaminate levels exceed exposure limits. Follow respirator manufacturer's directions and observe OSHA regulations for respirator use (29 cfr 1910.134).

### **Work Hygienic Practices:**

Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State:	Liquid
Color:	Liquid in assorted colors by part number
Odor:	Typical
Odor Threshold:	Not available
pH:	Not available
Melting Point:	Not applicable
Boiling Point:	180°F
Flash Point and Method:	54°F TCC
Evaporation Rate:	Not available
Flammability(Solid/Gas):	Not applicable
Flammable Limits:	1.0 – 12.0
Vapor Pressure:	Not available
Vapor Density:	Heavier Than Air
Density (lbs/gl):	8.0 – 10.0
Specific Gravity:	0.97 – 1.20
% Solubility in Water:	Not available
Octanol/Water Partition Coefficient:	Not available
Auto-Ignition Temperature:	Not available
Decomposition Temperature:	Not available

Viscosity: 65 – 68 KU  
 VOC INFORMATION: VOC (both Actual and Regulatory) as supplied, varies by color. Please see information on product label for specific VOC contents.

## **SECTION 10: STABILITY AND REACTIVITY**

### **Hazardous Polymerization:**

Under normal conditions of storage and use, hazardous polymerization will not occur.

### **Conditions to Avoid:**

Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke, extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, tools, appliances and any other possible sources of ignition prior to spray application, during use and until all vapors are exhausted from the area.

### **Chemical Stability:**

The product is stable. Avoid heat, open flame, sparks, static electricity, freezing.

### **Hazardous Decomposition Products:**

Carbon monoxide, carbon dioxide, and possible oxides of nitrogen.

### **Incompatible Materials:**

Alkaline materials, strong acids and oxidizing materials.

### **Possibility of Hazardous Reactions:**

Under normal conditions of use and storage, hazardous reactions will not occur.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Available ingredient data is listed below:

### **BUTYL CELLOSOLVE(111-76-2)**

Acute Dermal Toxicity	LD50: >2,000 mg/kg (guinea pig)	
Acute Inhalation Toxicity	LC0: >3.1 mg/l 1hrs (guinea pig)	Exposure to vapor may cause irritation of the eyes, nose, or throat. Inhalation may result in dizziness, headache, weakness, nausea and vomiting.
Acute Oral Toxicity	LD50: 1,1414 mg/kg (guinea pig)	Category 4.
Target Organ, Single Exposure	Central Nervous System	Harmful if swallowed. Ingestion may cause weakness, confusion, anxiety, decreased blood pressure, and CNS depression with collapse and coma.
Eye Irritation	Category 2A	Category 3
Skin Irritation	Category 2	High concentrations may cause central nervous system depression.
		Causes serious eye irritation.
		Causes skin irritation.

### **HIGH FLASH NAPHTHA(64742-95-6)**

Acute Dermal Toxicity	LD50: >2,000 mg/kg (rabbit)	Irritating to skin.
Acute Oral Toxicity	LD50: >5,000 mg/kg (rat)	
Aspiration Toxicity	Category 1	May be fatal if swallowed and enters airways.
Eye Irritation	Category 2A	Causes serious eye irritation.
Skin Irritation	Category 2	Causes skin irritation.
Carcinogenicity Classification	IARC Group 2B	Contains Cumene, (CAS No. 98-82-8), which is classified as possibly carcinogenic to humans.

### **ISOPROPYL ALCOHOL(67-63-0)**

Acute Dermal Toxicity	LD50 12,800 mg/kg (rabbit)	May cause skin irritation.
Acute Inhalation Toxicity	LC50 16000 ppm (rat)	
Acute Oral Toxicity	LD50 5,045 mg/kg (rat)	
Target Organ, Single Exposure	Central Nervous System	Category 3 May cause drowsiness or dizziness.
Eye Irritation	Category 2A	Causes serious eye irritation.
Symptoms of Overexposure	Headache, dizziness, tiredness, nausea and vomiting.	

### **TITANIUM DIOXIDE(13463-67-7)**

Acute Dermal Toxicity	LD50: >5,000 mg/kg (rabbit)	
Acute Inhalation Toxicity	LC50: >6.8 mg/l 4hrs (rat)	
Acute Oral Toxicity	LD50: >5,000 mg/kg (rat)	
Carcinogenicity Classification	IARC Group 2B	Possibly carcinogenic to humans.

### **XYLENE(1330-20-7)**

Acute Dermal Toxicity	1,100 mg/kg	Category 4 Harmful by skin absorption.
Acute Inhalation Toxicity	LC50 6700 ppm 4hrs (rat)	Category 4 Harmful if inhaled.
Acute Oral Toxicity	LD50 3,523 mg/kg (rat)	
Aspiration Toxicity	Category 1	May be fatal if swallowed and enters airways.
Target Organ, Single Exposure	Respiratory System	Category 3 May cause respiratory irritation.
Target Organ, Repeated Exposure	Liver, Kidney, Central Nervous System	Category 2 May cause damage to organs through prolonged or repeated exposure.
Eye Irritation	Category 2A	Causes serious eye irritation.
Skin Irritation	Category 2	Causes skin irritation.
Carcinogenicity Classification	IARC Group 2B	Possibly carcinogenic to humans.

## **SECTION 12: ECOLOGICAL INFORMATION**

Available ingredient data is listed below:

### **BUTYL CELLOSOLVE(111-76-2)**

Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 1,474 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50 1,800 mg/l 48hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	EC50 911 mg/l 72hrs
Persistence and degradability	Biodegradability	Readily
Bioaccumulative potential	Partition coefficient: n-octanol/water	log Pow: 0.83

### **HIGH FLASH NAPHTHA(64742-95-6)**

Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LL50: 10 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EL50: 4.5 mg/l 48hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	EL50: 3.1 mg/l 72hrs
Persistence and degradability	Biodegradability	Readily
Bioaccumulation Potential	Partition coefficient: n-octanol/water	log Pow: 3.42 (25 C)

**ISOPROPYL ALCOHOL(67-63-0)**

Toxicity to fish  
 Toxicity to daphnia and other aquatic invertebrate  
 Toxicity to algae  
 Persistence and degradability  
 Bioaccumulative potential

Pimephales promelas (fathead minnow)  
 Daphnia magna (Water flea)  
 No Data Available  
 Biodegradability  
 Bioaccumulation

LC50: >1,000 mg/l 96hrs  
 LC50: >100 mg/l 48hrs  
 No Data Available  
 Readily  
 Bioaccumulation is unlikely

**XYLENE(1330-20-7)**

Toxicity to fish  
 Toxicity to daphnia and other aquatic invertebrate  
 Toxicity to algae  
 Persistence and degradability  
 Bioaccumulative potential

Oncorhynchus mykiss (rainbow trout)  
 Daphnia magna (Water flea)  
 Pseudokirchneriella subcapitata (green algae)  
 Biodegradability  
 Partition coefficient: n-octanol/water

LC50: 2.6 mg/l 96hrs  
 IC50: 1 mg/l 24hrs  
 EC50: 4.36 mg/l 73hrs  
 Readily  
 log Pow: 2.77 - 3.15

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Recommendations:** The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection, waste disposal legislation and any regional local authority requirements. Empty containers should be disposed of through an approved waste management facility. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, ensure conformity to all applicable hazardous waste regulations, and consult your local or regional authorities.

**SECTION 14: TRANSPORT INFORMATION**

UN NUMBER: UN1263

UN PROPER SHIPPING NAME: PAINT

TRANSPORT HAZARD CLASS: 3

PACKING GROUP: II

**SPECIAL PRECAUTIONS:** The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the shipper and the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Local Government regulations and rules should prevail.

**SECTION 15: REGULATORY INFORMATION****United States Federal Regulations:**

**OSHA:** OSHA Hazard Communication Standard 29 CFR 1910.1200  
 A component(s) of this product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Toxic Substance Control Act (TSCA):**

All components of this product are listed or are exempt from Listing on the TSCA Inventory.

**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA RQ - 40 CFR302.4(a):** List of Hazardous Substances and Reportable Quantities (RQ)

BUTYL CELLOSOLVE	111-76-2	Glycol Ethers N230
XYLENE	1330-20-7	100 lbs

**SARA Section 311/312 Hazard Category - 40 CFR 370.2**

This product is considered, under applicable definitions, to meet the following categories:  
 Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**SARA 313 Components - 40 CFR 372.65**

This product contains the following substances subject to the reporting requirements of Section 313 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and 40 CFR 372:

BUTYL CELLOSOLVE	111-76-2 N230
HIGH FLASH NAPHTHA	64742-95-6
Contains:1,2,4-Trimethylbenzene	95-63-6
XYLENE	1330-20-7
Contains: Ethyl Benzene	100-41-4

**STATE REGULATIONS:**

**California Proposition 65:** WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

HIGH FLASH NAPHTHA	64742-95-6
Contains:1,2,4-Trimethylbenzene	95-63-6
TITANIUM DIOXIDE	13463-67-7
XYLENE	1330-20-7
Xylene Component: ETHYL BENZENE	100-41-4

**New Jersey, Pennsylvania, Massachusetts**

BUTYL CELLOSOLVE	111-76-2
HIGH FLASH NAPHTHA	64742-95-6
Contains:1,2,4-Trimethylbenzene	95-63-6
ISOPROPYL ALCOHOL	67-63-0
TITANIUM DIOXIDE	13463-67-7
XYLENE	1330-20-7
Xylene Component: ETHYL BENZENE	100-41-4

**SECTION 16: OTHER INFORMATION****HMIS RATING**

<b>Health:</b>	<b>3</b>
<b>Flammability:</b>	<b>3</b>
<b>Personal Hazard:</b>	<b>1</b>
<b>Personal Protection:</b>	<b>J</b>

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, \* = Chronic

DISCLAIMER: The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date. Coventry Coatings Corp. makes no representation, warranty or guarantee as to the completeness or accuracy thereof. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

DATE ISSUED: 5/29/2015  
Version No.: 2015AE-1