




View (M)SDS Section : [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#)

## SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Aluminum Oxide Coated Abrasive  
**MSDS Manufacturer Number:** 1066700\_ALCOAT001ZN  
**Manufacturer Name:** Saint-Gobain Abrasives, Inc.  
**Address:** 1 New Bond Street  
Worcester, MA 01615  
**Website:** www.Nortonabrasives.com  
**General Phone Number:** 508-795-5000  
**Emergency Phone Number:** 508-795-5000  
**MSDS Creation Date:** November 15, 2010  
**MSDS Revision Date:** July 01, 2013



HMIS	
Health Hazard	1
Fire Hazard	0
Reactivity	1
Personal Protection	X

## SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Zinc stearate	557-05-1	3 - 13 by weight	209-151-9
Animal Glue Bond	N/A	5 - 30 by weight	
Aluminum Oxide, Non-fibrous	1344-28-1	10 - 30 by weight	215-691-6
Cloth or Paper Backing	N/A	30 - 60 by weight	
Urea-formaldehyde polymer	9011-05-6	5 - 30 by weight	

## SECTION 3 : HAZARDS IDENTIFICATION

### Potential Health Effects:

**Eye:** Dust may cause slight irritation.

**Skin:** Dust from this product may cause temporary mechanical irritation.

**Inhalation:** Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.

**Ingestion:** Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

**Chronic Health Effects:** Chronic health effects are not expected as long as good hygiene and proper safety precautions are practiced.

### **Urea-formaldehyde polymer**

**Chronic Health Effects:** For products containing Urea/Formaldehyde resin, dust generated from intended use may contain trace amounts of formaldehyde which under excessive exposure may cause skin sensitization and airway obstruction.

---

---

## **SECTION 4 : FIRST AID MEASURES**

---

---

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists.

**Skin Contact:** Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

**Inhalation:** If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.

**Ingestion:** Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.

**Note to Physicians:** No information available.

---

---

## **SECTION 5 : FIRE FIGHTING MEASURES**

---

---

**Flammable Properties:** Non Flammable.

**Flash Point:** Does not apply.

**Auto Ignition Temperature:** Not determined.

**Lower Flammable/Explosive Limit:** Not available.

**Upper Flammable/Explosive Limit:** Not available.

**Extinguishing Media:** Use any extinguishing media appropriate for the surrounding fires.

**Unsuitable Media:** None.

**Protective Equipment:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### **NFPA Ratings:**

NFPA Health: 0

NFPA Flammability: 0

NFPA Reactivity: 1

NFPA Other:

---

---

## **SECTION 6 : ACCIDENTAL RELEASE MEASURES**

---

---

**Methods for containment:** Containment of this material should not be necessary.

**Methods for cleanup:** Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Dispose of in accordance with Local, State, Federal and Provincial regulations.

## SECTION 7 : HANDLING and STORAGE

<b>Handling:</b>	<p>Always HANDLE AND STORE wheels in a CAREFUL manner.            Always VISUALLY INSPECT all wheels before mounting.            Always CHECK MACHINE SPEED against the established maximum safe operating speed MARKED ON THE WHEEL.            Always CHECK MOUNTING FLANGES for equal and correct diameter.            Always USE MOUNTING BLOTTERS.            Always be sure WORK REST is properly adjusted.            Always USE A SAFETY GUARD covering at least one-half of the grinding wheel.            Always allow NEWLY MOUNTED WHEELS to run at operating speed, with guard in place, for at least one minute before grinding.            Always TURN OFF COOLANT before stopping wheel to avoid creating an out-of-balance wheel.</p>
<b>Storage:</b>	No special storage conditions required.
<b>Hygiene Practices:</b>	Wear suitable gloves and eye/face protection.

## SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

<b>Engineering Controls:</b>	General dilution ventilation and/or local exhaust ventilation should be provided as necessary to maintain exposures below occupational exposure limits.
<b>Eye/Face Protection:</b>	Always WEAR SAFETY GLASSES or some type of eye protection when grinding.
<b>Skin Protection Description:</b>	Protective gloves. Long sleeved shirt and long pants.
<b>Respiratory Protection:</b>	When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.
<b>Other Protective:</b>	Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).
<b>General Hygiene Considerations:</b>	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

### EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline ACGIH	Quebec Canada	Ontario Canada	Alberta Canada
Zinc stearate	PEL-TWA: 5 mg/m <sup>3</sup> Respirable fraction (R) PEL-TWA: 15 mg/m <sup>3</sup> Total particulate/dust (T)	TLV-TWA: 10 mg/m <sup>3</sup>	VEMP-TWA: 10 mg/m <sup>3</sup>		OEL-TWA: 10 mg/m <sup>3</sup>
Aluminum Oxide, Non-fibrous	PEL-TWA: 5 mg/m <sup>3</sup> Respirable fraction (R) PEL-TWA: 15 mg/m <sup>3</sup> Total particulate/dust (T)	TLV-TWA: 10 mg/m <sup>3</sup>	VEMP-TWA: 10 mg/m <sup>3</sup> Total particulate/dust (T)	OEL-TWAEV: 10 mg/m <sup>3</sup> Total particulate/dust (T)	OEL-TWA: 10 mg/m <sup>3</sup>
Ingredient	Mexico	British Columbia Canada			
Zinc stearate	LMPE-PPT: 10 mg/m <sup>3</sup> LMPE-CT: 20 mg/m <sup>3</sup>	OEL-TWA: 10 mg/m <sup>3</sup> Total particulate/dust (T) OEL-TWA: 3 mg/m <sup>3</sup> Respirable fraction (R) OEL-STEL: 20 mg/m <sup>3</sup> Total particulate/dust (T)			

Aluminum Oxide, Non-fibrous	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)			
-----------------------------	---	---	--	--	--

## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Solid article.  
 Odor: Odorless.  
 Flash Point: Does not apply.  
 Auto Ignition Temperature: Not determined.

## SECTION 10 : STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.  
 Hazardous Polymerization: Hazardous polymerization does not occur.  
 Special Decomposition Products: In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the grinding wheel components. Coolants may produce other decomposition products.

## SECTION 11 : TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

<b>Carcinogens:</b>	<b>ACGIH</b>	<b>NIOSH</b>	<b>OSHA</b>	<b>IARC</b>	<b>NTP</b>		

### Zinc stearate :

RTECS Number: ZH5200000  
 Ingestion: Oral - Rat LD50: >10 gm/kg [Details of toxic effects not reported other than lethal dose value]  
 Oral - Mouse LD50: >10 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

### Animal Glue Bond :

RTECS Number: LK3651000

### Aluminum Oxide, Non-fibrous :

RTECS Number: VW0450000  
 Inhalation: Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS)

### Urea-formaldehyde polymer :

RTECS Number: YU1610000  
 Eye: Eye - Rabbit Standard Draize test.: 100 uL/24H [severe] (RTECS)

<b>Skin:</b>	Administration onto the skin - Rabbit Standard Draize test.: 500 mg/24H [severe] Administration onto the skin - Rat LD50 : >2100 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
<b>Inhalation:</b>	Inhalation - Rat LC50 : >167 mg/m <sup>3</sup> /4H [Details of toxic effects not reported other than lethal dose value] (RTECS)
<b>Ingestion:</b>	Oral - Rat LD50 : 8394 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50 : 6361 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

---

---

## SECTION 12 : ECOLOGICAL INFORMATION

---

---

<b>Biodegradation:</b>	Resin bonded materials demonstrate similar degradation rates as Phenolic plastics.
------------------------	--

---

---

## SECTION 13 : DISPOSAL CONSIDERATIONS

---

---

<b>Waste Disposal:</b>	Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.
------------------------	---

---

---

## SECTION 14 : TRANSPORT INFORMATION

---

---

<b>DOT Shipping Name:</b>	Not regulated as hazardous material for transportation.
<b>DOT UN Number:</b>	Not regulated as hazardous material for transportation.
<b>IATA Shipping Name:</b>	Not regulated as hazardous material for transportation.
<b>Canadian Shipping Name:</b>	This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

---

---

## SECTION 15 : REGULATORY INFORMATION

---

---

### Zinc stearate :

<b>TSCA Inventory Status:</b>	Listed
<b>Section 313:</b>	EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.
<b>Massachusetts:</b>	Listed
<b>Pennsylvania:</b>	Listed
<b>Canada DSL:</b>	Listed
<b>Canada IDL:</b>	Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.1725(1504)
<b>EC Number:</b>	209-151-9

### Aluminum Oxide, Non-fibrous :

<b>TSCA Inventory Status:</b>	Listed
<b>New Jersey:</b>	Listed: NJ Hazardous List; Substance Number: 2891
<b>Massachusetts:</b>	Listed

Pennsylvania: Listed  
Canada DSL: Listed  
Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)  
EC Number: 215-691-6

**Urea-formaldehyde polymer :**

TSCA Inventory Status: Listed  
Canada DSL: Listed

---

---

**SECTION 16 : ADDITIONAL INFORMATION**

---

---

MSDS Creation Date: November 15, 2010  
MSDS Revision Date: July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.

UPC Number = 63642557611