




**View (M)SDS Section :**    [1](#)   [2](#)   [3](#)   [4](#)   [5](#)   [6](#)   [7](#)   [8](#)   [9](#)   [10](#)   [11](#)   [12](#)   [13](#)   [14](#)   [15](#)   [16](#)

**SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:**                    **Coated Abrasive**  
**MSDS Manufacturer**  
**Number:**                            983532\_CA\_All  
**Manufacturer Name:**            Saint-Gobain Abrasives, Inc.  
**Address:**                            1 New Bond Street  
    Worcester, MA 01615  
**Website:**                            www.Nortonabrasives.com  
**General Phone Number:**        508-795-5000  
**Emergency Phone Number:**    508-795-5000  
**MSDS Creation Date:**            November 30, 2009  
**MSDS Revision Date:**            July 01, 2013



**HMIS**

Health Hazard	1
Fire Hazard	0
Reactivity	0
Personal Protection	X

**SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Ingredient Percent	EC Num.
Sulfates/Sulfides	No Data	5.0 - 10 by weight	
Zinc stearate	557-05-1	5.0 - 10 by weight	209-151-9
Urea-formaldehyde polymer	9011-05-6	10.0 - 30 by weight	
Paraffin waxes and hydrocarbon waxes	8002-74-2	1.0 - 5 by weight	232-315-6
Aluminum Oxide, Non-fibrous	1344-28-1	10.0 - 30 by weight	215-691-6
Paper - Processed Cellulose	9004-34-6	10.0 - 30 by weight	232-674-9

**SECTION 3 : HAZARDS IDENTIFICATION**

**Potential Health Effects:**

**Eye:**                                    Dust may cause slight irritation.  
**Skin:**                                    Dust from this product may cause temporary mechanical irritation.  
**Inhalation:**                            Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.  
**Ingestion:**                            Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

**Chronic Health Effects:** Chronic health effects are not expected as long as good hygiene and proper safety precautions are practiced.

### **Urea-formaldehyde polymer**

**Chronic Health Effects:** For products containing Urea/Formaldehyde resin, dust generated from intended use may contain trace amounts of formaldehyde which under excessive exposure may cause skin sensitization and airway obstruction.

---

---

## **SECTION 4 : FIRST AID MEASURES**

---

---

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists.

**Skin Contact:** Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

**Inhalation:** If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.

**Ingestion:** Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.

**Note to Physicians:** No information available.

---

---

## **SECTION 5 : FIRE FIGHTING MEASURES**

---

---

**Flammable Properties:** Non Flammable.

**Flash Point:** Does not apply.

**Auto Ignition Temperature:** Not determined.

**Lower Flammable/Explosive Limit:** Not available.

**Upper Flammable/Explosive Limit:** Not available.

**Extinguishing Media:** Use any extinguishing media appropriate for the surrounding fires.

**Unsuitable Media:** None.

**Protective Equipment:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### **NFPA Ratings:**

**NFPA Health:** 1

**NFPA Flammability:** 0

**NFPA Reactivity:** 1

**NFPA Other:**

---

---

## **SECTION 6 : ACCIDENTAL RELEASE MEASURES**

---

---

**Methods for containment:** Containment of this material should not be necessary.

**Methods for cleanup:** Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Dispose of in accordance with Local, State, Federal and Provincial regulations.

## SECTION 7 : HANDLING and STORAGE

<b>Handling:</b>	Handle with adequate ventilation for nuisance dust.
<b>Storage:</b>	No special storage conditions required.
<b>Hygiene Practices:</b>	Wear suitable gloves and eye/face protection.

## SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

<b>Engineering Controls:</b>	General dilution ventilation and/or local exhaust ventilation should be provided as necessary to maintain exposures below occupational exposure limits.
<b>Eye/Face Protection:</b>	Always WEAR SAFETY GLASSES or some type of eye protection when grinding.
<b>Skin Protection Description:</b>	Protective gloves. Long sleeved shirt and long pants.
<b>Respiratory Protection:</b>	When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.
<b>Other Protective:</b>	Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).
<b>General Hygiene Considerations:</b>	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

### EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Zinc stearate	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3	
Paraffin waxes and hydrocarbon waxes			TLV-TWA: 2 mg/m3	VEMP-TWA: 2 mg/m3	
Aluminum Oxide, Non-fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Paper - Processed Cellulose	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)	REL-TWA: 10 mg/m3 Total particulate/dust (T) REL-TWA: 5 mg/m3 Respirable fraction (R)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 ppm Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Ingredient	Alberta Canada	Mexico	British Columbia Canada		
Zinc stearate	OEL-TWA: 10 mg/m3	LMPE-PPT: 10 mg/m3 LMPE-CT: 20 mg/m3	OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-STEL: 20 mg/m3 Total particulate/dust (T)		
Paraffin waxes and hydrocarbon waxes		LMPE-PPT: 2 mg/m3 LMPE-CT: 6 mg/m3	OEL-TWA: 2 mg/m3		

Aluminum Oxide, Non-fibrous	OEL-TWA: 10 mg/m <sup>3</sup>	MPE-PPT: 0.1 mg/m <sup>3</sup> Respirable fraction (R)	OEL-TWA: 3 mg/m <sup>3</sup> Respirable fraction (R) OEL-TWA: 10 mg/m <sup>3</sup> OEL-TWA: 10 mg/m <sup>3</sup> Total particulate/dust (T) OEL-STEL: 20 mg/m <sup>3</sup> Total particulate/dust (T)		
Paper - Processed Cellulose	OEL-TWA: 10 mg/m <sup>3</sup>	LMPE-PPT: 10 mg/m <sup>3</sup> LMPE-CT: 20 mg/m <sup>3</sup>	OEL-TWA: 3 mg/m <sup>3</sup> Respirable fraction (R) OEL-TWA: 10 mg/m <sup>3</sup> Total particulate/dust (T)		

---



---

## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

---



---

<b>Physical State Appearance:</b>	Solid article.
<b>Odor:</b>	Odorless.
<b>Flash Point:</b>	Does not apply.
<b>Auto Ignition Temperature:</b>	Not determined.

---



---

## SECTION 10 : STABILITY and REACTIVITY

---



---

<b>Chemical Stability:</b>	Stable under normal conditions.
<b>Hazardous Polymerization:</b>	Hazardous polymerization does not occur.
<b>Conditions to Avoid:</b>	Keep away from heat, sparks, or open flame.
<b>Special Decomposition Products:</b>	In use, dust and decomposing odors may be generated. Thermal decomposition may produce trace amounts of phenol and formaldehyde. In most cases, the material removed from the workplace will be significantly greater than the grinding wheel components. Coolants may produce other decomposition products.

---



---

## SECTION 11 : TOXICOLOGICAL INFORMATION

---



---

<b>Acute Toxicity:</b>	This product has not been tested for its toxicity.
<b><u>Zinc stearate :</u></b>	
<b>RTECS Number:</b>	ZH5200000
<b>Ingestion:</b>	Oral - Rat LD50: >10 gm/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50: >10 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
<b><u>Urea-formaldehyde polymer :</u></b>	
<b>RTECS Number:</b>	YU1610000
<b>Eye:</b>	Eye - Rabbit Standard Draize test.: 100 uL/24H [severe] (RTECS)
<b>Skin:</b>	Administration onto the skin - Rabbit Standard Draize test.: 500 mg/24H [severe] Administration onto the skin - Rat LD50 : >2100 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
<b>Inhalation:</b>	Inhalation - Rat LC50 : >167 mg/m <sup>3</sup> /4H [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Ingestion:** Oral - Rat LD50 : 8394 mg/kg [Details of toxic effects not reported other than lethal dose value]  
Oral - Mouse LD50 : 6361 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Paraffin waxes and hydrocarbon waxes :**

**RTECS Number:** RV0350000

**Eye:** Eye - Rabbit Standard Draize test.: 100 mg/24H (RTECS)

**Skin:** Administration onto the skin - Rabbit Standard Draize test.: 500 mg/24H (RTECS)

**Aluminum Oxide, Non-fibrous :**

**RTECS Number:** BD1200000

**Inhalation:** Inhalation - Rat TCLo: 200 mg/m<sup>3</sup>/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS)

**Paper - Processed Cellulose :**

**RTECS Number:** FJ5691460

**Inhalation:** Inhalation - Rat LC50: >5800 mg/m<sup>3</sup>/4H [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Ingestion:** Oral - Rat LD50: >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

---

---

**SECTION 12 : ECOLOGICAL INFORMATION**

---

---

**Ecotoxicity:** No ecotoxicity data was found for the product.

---

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

---

---

**Waste Disposal:** Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

---

---

**SECTION 14 : TRANSPORT INFORMATION**

---

---

**DOT Shipping Name:** Not regulated as hazardous material for transportation.

**DOT UN Number:** Not regulated as hazardous material for transportation.

**IATA Shipping Name:** Not regulated as hazardous material for transportation.

**Canadian Shipping Name:** This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

---

---

**SECTION 15 : REGULATORY INFORMATION**

---

---

**Inventory Status**

	<b>EINECS Number</b>	<b>Canada DSL</b>	<b>TSCA Inventory Status</b>		
Zinc stearate		Listed	Listed		
Urea-formaldehyde polymer		Listed	Listed		

Paraffin waxes and hydrocarbon waxes		Listed	Listed		
Aluminum Oxide, Non-fibrous		Listed	Listed		
Paper - Processed Cellulose	232-674-9	Listed	Listed		

**Zinc stearate :**

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.1725(1504)

Section 313: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

**Aluminum Oxide, Non-fibrous :**

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

**Zinc stearate :**

EC Number: 209-151-9

**Paraffin waxes and hydrocarbon waxes :**

EC Number: 232-315-6

**Aluminum Oxide, Non-fibrous :**

EC Number: 215-691-6

**Paper - Processed Cellulose :**

EC Number: 232-674-9

**State Right To Know**

	PA	MA	NJ		
Zinc stearate	Listed	Listed			
Paraffin waxes and hydrocarbon waxes	Listed	Listed			
Aluminum Oxide, Non-fibrous	Listed	Listed	Listed: NJ Hazardous List; Substance Number: 2891		
Paper - Processed Cellulose	Listed	Listed			

**SECTION 16 : ADDITIONAL INFORMATION**

MSDS Creation Date: November 30, 2009

MSDS Revision Date: July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.

UPC Number = 66261131691