


**View (M)SDS Section :**     [1](#)   [2](#)   [3](#)   [4](#)   [5](#)   [6](#)   [7](#)   [8](#)   [9](#)   [10](#)   [11](#)   [12](#)   [13](#)   [14](#)   [15](#)   [16](#)

## SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

**Product Name:**                    **Scuff Gel**  
**Product Code:**                    05376  
**MSDS Manufacturer Number:**    05376  
**Manufacturer Name:**            Saint-Gobain Abrasives, Inc.  
**Address:**                            1 New Bond Street  
                                               Worcester, MA 01615  
**Website:**                            www.Nortonabrasives.com  
**General Phone Number:**        508-795-5000  
**Emergency Phone Number:**    508-795-5000  
**MSDS Creation Date:**            August 09, 2010  
**MSDS Revision Date:**            July 01, 2013



**HMIS**

<b>Health Hazard</b>	<b>1</b>
<b>Fire Hazard</b>	<b>1</b>
<b>Reactivity</b>	<b>0</b>
<b>Personal Protection</b>	<b>1</b>

## SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
d-Limonene Technical grade	5989-27-5	1 - 5 by weight	
Glycerin	56-81-5	1 - 5 by weight	
Polyethylene Glycol 400	25322-68-3	1- 10 by weight	
Crystalline Silica, Quartz	14808-60-7	1 - 10 by weight	238-878-4
Water		60 - 100 by weight	

## SECTION 3 : HAZARDS IDENTIFICATION

**Emergency Overview:**            WARNING! Potential Sensitizer. Irritant.  
**Route of Exposure:**                Eyes. Skin. Inhalation. Ingestion.  
**Potential Health Effects:**

**Eye:**                                    Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury..

**Skin:**                                    Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible.  
 May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.

**Inhalation:** Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.

**Ingestion:** Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.

---

---

## SECTION 4 : FIRST AID MEASURES

---

---

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

**Skin Contact:** Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

---

---

## SECTION 5 : FIRE FIGHTING MEASURES

---

---

**Auto Ignition Temperature:** Not determined.

**Lower Flammable/Explosive Limit:** Not determined.

**Upper Flammable/Explosive Limit:** Not determined.

**Fire Fighting Instructions:** Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

**Extinguishing Media:** Use carbon dioxide (CO<sub>2</sub>) or dry chemical when fighting fires involving this material.

**Unsuitable Media:** Water or foam may cause frothing.

**Protective Equipment:** As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

### **NFPA Ratings:**

NFPA Health: 1

NFPA Flammability: 1

NFPA Reactivity: 0

---

---

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

---

---

**Personnel Precautions:** Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.

**Environmental Precautions:** Avoid runoff into storm sewers, ditches, and waterways.

**Spill Cleanup Measures:** Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.

**Other Precautions:** Pump or shovel to storage/salvage vessels.

---

---

## SECTION 7 : HANDLING and STORAGE

<b>Handling:</b>	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
<b>Storage:</b>	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
<b>Special Handling Procedures:</b>	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
<b>Hygiene Practices:</b>	Wash thoroughly after handling.

---



---

## SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

---



---

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
<b>Skin Protection Description:</b>	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
<b>Respiratory Protection:</b>	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
<b>Other Protective:</b>	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

### EXPOSURE GUIDELINES

#### Crystalline Silica, Quartz :

<b>Guideline ACGIH:</b>	TLV-TWA: 0.025 mg/m <sup>3</sup> (Respirable)
<b>Guideline OSHA:</b>	PEL-TWA: [30 mg/m <sup>3</sup> ]/{% SiO <sub>2</sub> } + 2] - Total dust [10 mg/m <sup>3</sup> ]/{% SiO <sub>2</sub> } + 2] - Respirable dust

---



---

## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

---



---

<b>Physical State:</b>	Paste
<b>Physical State Appearance:</b>	Thick Paste
<b>Color:</b>	White
<b>Odor:</b>	Orange Scent
<b>Specific Gravity:</b>	1.45
<b>pH:</b>	8-9
<b>Auto Ignition Temperature:</b>	Not determined.

---



---

## SECTION 10 : STABILITY and REACTIVITY

---



---

<b>Chemical Stability:</b>	Stable under normal temperatures and pressures.
<b>Hazardous Polymerization:</b>	Not reported.

**Conditions to Avoid:** Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.

**Incompatible Materials:** Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.

---

---

## SECTION 11 : TOXICOLOGICAL INFORMATION

---

---

### Crystalline Silica, Quartz :

**ACGIH:** A2 - Suspected Human Carcinogen

**NIOSH:** NIOSH carcinogen

**OSHA:** No Data

**IARC:** Group 1 - Carcinogenic to humans.

**NTP:** K - Known to be a human carcinogen.

**Carcinogenicity:** While an unlikely route of exposure, if inhaled, Crystalline Silica, Quartz may cause delayed respiratory disease (silicosis, lung fibrosis).

### Crystalline Silica, Quartz :

**Inhalation:** Inhalation - Rat TLo: 200 mg/kg; Lungs, Thorax, or Respiration - Fibrosis, focal (pneumoconiosis) Lungs, Thorax, or Respiration - Other changes Nutritional and Gross Metabolic - Changes in iron (RTECS)

**Ingestion:** Oral - Rodent rat TDLo - Lowest published toxic dose: 120 gm/kg - [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes ] (RTECS)

**Chronic Effects:** The International Agency for Research on Cancer (IARC) recently reviewed existing epidemiological data and concluded that crystalline silica inhaled in the form of quartz from occupational sources is a known human carcinogen (Group 1). In making the assessment, IARC noted that carcinogenicity was not detected in all industrial circumstances studies. However, IARC reported that a majority of studies indicated an elevated mortality for lung cancer among silica-exposed workers. IARC noted that increased rates of lung cancer were reported among some workers in oremines, quarries, foundries, ceramics, granite and stone cutting industries. The workers in some of these occupational studies were exposed to other potential respiratory carcinogens such as arsenic, radon, diesel exhaust, polycyclic aromatic hydrocarbons or cadmium. IARC reviewed animal studies and concluded that there is sufficient evidence in experimental animals for the carcinogenicity of quartz.

---

---

## SECTION 12 : ECOLOGICAL INFORMATION

---

---

**Ecotoxicity:** No ecotoxicity data was found for the product.

**Environmental Fate:** No environmental information found for this product.

---

---

## SECTION 13 : DISPOSAL CONSIDERATIONS

---

---

**Waste Disposal:** Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

**RCRA Number:** None.

---

---

## SECTION 14 : TRANSPORT INFORMATION

---

---

DOT Shipping Name: Non regulated.  
DOT UN Number: Non regulated.  
  
IATA Shipping Name: Non regulated.  
IATA UN Number: Non regulated.

---

---

## SECTION 15 : REGULATORY INFORMATION

---

---

### Crystalline Silica, Quartz :

TSCA Inventory Status: Listed

California PROP 65: The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):  
WARNING! This product contains a chemical known to the State of California to cause cancer.

New Jersey: No Data

Massachusetts: Listed

Pennsylvania: Listed

Minnesota: No Data

Illinois: No Data

Rhode Island: Listed

Canada DSL: Listed

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 1%. Item: 1406(1491)

EC Number: 238-878-4

---

---

## SECTION 16 : ADDITIONAL INFORMATION

---

---

MSDS Creation Date: August 09, 2010  
MSDS Revision Date: July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.

UPC Number = 07660705376