



Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

1 Identification

- **Product identifier**
- **Trade name:** 935K0099 JET BLACK FACTORY PAC
- **Article number:** 935K0099
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
5195 West 4700 South
KEARNS, UT 84118
USA
www.lusid.biz
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

n-butyl acetate
 Carbon black
 Solvent naphtha (petroleum), light arom.
 acetone
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Highly flammable liquid and vapor.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0
 Fire = 3
 Reactivity = 0

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = *0
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	n-butyl acetate	10-25%
110-43-0	heptan-2-one	10-25%
67-64-1	acetone	2.5-10%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2.5-10%
1333-86-4	Carbon black	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
67-64-1	acetone	200 ppm
1333-86-4	Carbon black	9 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene	130 ppm
7664-38-2	phosphoric acid	3 mg/m ³
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
122-99-6	2-Phenoxyethanol	1.5 ppm
100-41-4	ethylbenzene	33 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm

- **PAC-2:**

123-86-4	<i>n</i> -butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
67-64-1	acetone	3200* ppm
1333-86-4	Carbon black	99 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
7664-38-2	phosphoric acid	30 mg/m ³
77-58-7	dibutyltin dilaurate	8 mg/m ³
122-99-6	2-Phenoxyethanol	16 ppm
100-41-4	ethylbenzene	1100* ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm

- **PAC-3:**

123-86-4	<i>n</i> -butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
67-64-1	acetone	5700* ppm
1333-86-4	Carbon black	590 mg/m ³

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 4)

108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
7664-38-2	phosphoric acid	150 mg/m ³
77-58-7	dibutyltin dilaurate	48 mg/m ³
122-99-6	2-Phenoxyethanol	97 ppm
100-41-4	ethylbenzene	1800* ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 233 mg/m ³ , 50 ppm

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 5)

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction

· **Ingredients with biological limit values:**

67-64-1 acetone

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

USA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 6)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Black
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C (131 °F)

· Flash point: -17 °C (1.4 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 370 °C (698 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1 Vol %
Upper:	7.5 Vol %

· Vapor pressure at 20 °C (68 °F): 10.7 hPa (8 mm Hg)

· Density at 20 °C (68 °F): 1.0143 g/cm³ (8.4643 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents:	40.7 %
VOC content:	34.93 %
	406.6 g/l / 3.39 lb/gal

Solids content: 54.3 %

· Other information: No further relevant information available.

10 Stability and reactivity

· Reactivity: No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 7)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1333-86-4	Carbon black	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC



(Contd. of page 8)

- *Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | <p style="margin-left: 20px;">UN1263</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | <p style="margin-left: 20px;">Paint
PAINT</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center; margin-bottom: 10px;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids
3</p> |
| | |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center; margin-bottom: 10px;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids
3</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | <p style="margin-left: 20px;">II</p> |
| <ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: | <p style="margin-left: 20px;">No</p> |
| <ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category | <p style="margin-left: 20px;">Warning: Flammable liquids
33
F-E, S-E
B</p> |

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 10)

1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
77-58-7	dibutyltin dilaurate	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4 Carbon black

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

n-butyl acetate

Carbon black

Solvent naphtha (petroleum), light arom.

acetone

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Highly flammable liquid and vapor.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: 935K0099 JET BLACK FACTORY PAC

(Contd. of page 11)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 08/06/2018 / 2
- **Abbreviations and acronyms:**
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Muta. 1B: Germ cell mutagenicity – Category 1B
 Carc. 1B: Carcinogenicity – Category 1B
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- *** Data compared to the previous version altered.**

USA