



Premium Masking Solutions

Premium Trim Masking 10 MM

Q1® Premium Trim Masking is designed to facilitate trim masking situation including: inset door handles, windscreen, side mouldings, taillight, sidelight and headlight units allowing complete paint coverage under the moulding while protecting the front of the moulding from paint overspray.

Composed by a plastic strip on a self-adhesive tape and a flexible polyester band of 190 µm and a width of 10mm, thermal class B (130°C). Thanks to its characteristics the tape supports temperatures up to 110°C without leaving any residue.

For an easy application it is pre-cut every 38mm.



Features

- High Performance rubber-based adhesive
- Specially treated paper backing
- Temperature Resistance up to 110° C. (30 min.) 90° C. (60 min.)
- Pre-perforated for easy tear off
- Very flexible to follow contours and tight curves
- Self-dispensing box
- Easy lifting tab & tape

Benefits

- Resists moisture and solvents
- Prevents paint bridging to moulding, no bleed-through
- Conforms to curved surfaces without lifting or tearing
- One size fits all mouldings
- Quick application, no cutting tool needed
- Save time and labour cost of removing mouldings
- Eliminate visible paint edge

Available Colour

Sun Yellow

Temperature Resistance

30 min.	60 min.
110° C.	90° C.

Product Reference

Q1® Product Number	Q1® Product Description
TT01	10mm hard tab x 10 m – 72 roll/ case

Technical Data Sheet

Characteristics	Units	Std.Values	Toler	Test method
Total Weight	g/m ²	92	± 8%	ISO 536
Total Thickness	µm	125	± 10%	AFERA 5006
MD tensile strenght	N/cm	>28		AFERA 5004
MD elongation at break	%	>8		AFERA 5004
Adhesion to steel plate	N/cm	>2.2		AFERA 5001

How to



Watch our tutorial video on You Tube.

Scan the QR code with your smartphone to learn more about how to use our products.

Additional Information

Storage & Handling

Q1[®] Tapes must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 15 to 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 10°C. With a storage temperature lower than 10°C, it is always suggested temperature reconditioning of the tape at room temperature (15°C - 25 ° C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 23 °C, 50% humidity is considered 12 months Q1[®] Tapes does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1[®] Tapes believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1[®] Tapes has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Precautionary Information

Refer to Product label description and Material Safety Data Sheet for Health and Safety Information for a proper handling of product. MSDS info available at www.q1tapes.com

Product Use

Q1[®] Tapes would advise that there are many factors beyond Q1[®] Tapes' control but within the users knowledge that can affect the use and performance of Q1[®] Tapes products. Q1[®] Tapes remind the user of the products to make sure that the Q1[®] Tapes range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1[®] Tapes literature.