

01



Manufacturer's Name
 Sherwin-Williams Automotive
 101 Prospect Avenue N.W.
 Cleveland, Ohio 44115

Emergency Telephone Number
 (216) 566-2917
Information Telephone Number
 (216) 566-2902
Date of Preparation
 30-November-2001

Section 1 — Product Identification

PRODUCT NUMBER AND NAME

SC155 Plastic Surface Cleaner

Section 2 — Hazardous Ingredients

% Wt.	CAS No.	Ingredient Name	Vapor Pressure
1	34590-94-8	2-Methoxymethylethoxypropanol	0.4 mm Hg
		ACGIH TLV 100 ppm (skin)	
		ACGIH TLV 150 ppm (skin) STEL	
		OSHA PEL 100 ppm (skin)	
		OSHA PEL 150 ppm (skin) STEL	
6 §	112-34-5	2-(2-Butoxyethoxy)-ethanol	0.06 mm Hg
		ACGIH TLV Not Established	
		OSHA PEL Not Established	
1	Proprietary	Tripropylene Glycol Ether	0.02 mm Hg
		ACGIH TLV Not Established	
		OSHA PEL Not Established	

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

Section 3 — Hazards Identification

ROUTES OF EXPOSURE - Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. May be absorbed through the skin. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE - Irritation of eyes, skin and respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE - Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE - None generally recognized.

CANCER INFORMATION - For complete discussion of toxicology data refer to Section 11.

Section 4 — First Aid Measures

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
 If on SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Do not induce vomiting. Get medical attention immediately.

Section 5 — Fire Fighting Measures

FLAMMABILITY CLASSIFICATION - Not Applicable

FLASH POINT - > 200 °F

LEL N.Ap. UEL N.Ap.

EXTINGUISHING MEDIA - Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS - Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES - Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 — Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED - Remove all sources of ignition. Ventilate the area.

Section 7 — Handling and Storage

DOL STORAGE CATEGORY - Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING - Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section 8 — Exposure Controls/Personal Protection

PRECAUTIONS TO BE TAKEN IN USE - Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION - Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION - If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES - Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION - Wear safety spectacles with unperforated sideshields.

Section 9 — Physical and Chemical Properties

PRODUCT WEIGHT	12.0 lb/gal	EVAPORATION RATE	Slower than ether
SPECIFIC GRAVITY	1.45	VAPOR DENSITY	Heavier than air
BOILING POINT	210 - 610 °F	MELTING POINT	Not Available
VOLATILE VOLUME	97 %	SOLUBILITY IN WATER	N.Av.
HMS RATING	2 - 1 - 0	pH	10
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)			
Emitted VOC	0.7 lb/gal 84 g/l		

Section 10 - Stability and Reactivity

STABILITY - Stable

CONDITIONS TO AVOID - None known.

INCOMPATIBILITY - None known.

HAZARDOUS DECOMPOSITION PRODUCTS - By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will not occur

Section 11 — Toxicological Information

CHRONIC Health Hazards - No ingredient in this product is an IARC, NTP, or OSHA listed carcinogen.

Toxicology Data

CAS No.	Ingredient Name	LC50 RAT 4HR	LD50 RAT
34590-94-8	2-Methoxymethylethoxypropanol	Not Established	
			5135 mg/kg
112-34-5	2-(2-Butoxyethoxy)-ethanol	Not Established	
			5660 mg/kg
Proprietary	Tripropylene Glycol Ether	Not Established	
			3200 mg/kg

Section 12 — Ecological Information

No data available.

Section 13 — Disposal Considerations

WASTE DISPOSAL METHOD - Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 14 — Transport Information

No data available.

Section 15 — Regulatory Information

TSCA CERTIFICATION - All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 — Other Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.