

# U-POL®

## UP 0700 - FIBRAL LITE

### Sandable Fiber Glass Putty

#### Description

U-POL FIBRAL LITE is a short-strand fiber glass putty used for bridging holes in steel and fiber glass panels.

U-POL FIBRAL LITE putty forms a hard durable surface, however its short-strand formulation enables it to be easily applied and sanded.

U-POL FIBRAL LITE has been specially formulated for the professional it can be top coated with putty or directly top coated with paint.

#### Health and Safety Statement

FOR PROFESSIONAL USE ONLY. Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

#### Surface preparation and instructions for use

U-POL FIBRAL LITE putty can be used on the following :-

- Steel - degrease and abrade with 80 grit paper.
- Fully cured paint surfaces - degrease and sand with 180 grit paper.
- Glass Fiber - degrease and sand with 80 grit paper.

#### Mixing ratio

100% by weight U-POL FIBRAL LITE 3% by weight U-POL hardener for putty. The exact mixing ratio is not critical although over or under catalyzation may affect the gel time.

#### Tools

Mixing board, filler knife, plastic or rubber spreader.

#### Pot life

U-POL FIBRAL LITE is rapid curing and non shrinking once mixed, 4-5 mins. at 70°F with 3% hardener.

#### Drying time

Sandable after 20 mins. at 70°F.

#### Application

U-POL FIBRAL LITE is a smooth creamy putty it will not sag even on vertical surfaces.

#### Sanding

Begin sanding with 80 grit paper using finer grades to finish such as 120 then 220 grit, for rotary sanding equipment a hard back plate is recommended. Hand sanding can be done wet or dry.

#### Top-Coating

U-POL FIBRAL LITE can be top-coated with most paint systems.

#### Product codes

UP0700 (FIBL/3) - 3L Can.  
UP0766 (FIBL/2) - 946ml Can. (1 US Quart)

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064

Tel: (800) 340 7824; Fax: (800) 787 5150

Email: [sales-us@u-pol.com](mailto:sales-us@u-pol.com) Website: [www.u-pol.com](http://www.u-pol.com)