



Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

1 Identification

- **Product identifier**
- **Trade name:** 68004 SPARKLE SILVER H.O.K. B/C
- **Article number:** 68004
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
HIGH TECK PRODUCTS
PO BOX 24631
WEST PALM BEACH, FLORIDA 33416
USA
877-900-8325
info@highteckproducts.com
- **Information department:** Product safety department
- **Emergency telephone number:** 800 424-9300 (Chemtrec)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

Substances and mixtures which, in contact with water, emit flammable gases 2

H225 Highly flammable liquid and vapor.

H261 In contact with water releases flammable gas.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

Carcinogenicity 1B

Toxic to Reproduction 2

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.



GHS07

Eye Irritation 2A

Specific Target Organ Toxicity - Single Exposure 3

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

acetone
Naphtha (petroleum), hydrotreated heavy
toluene
n-butyl acetate

· **Hazard statements**

Highly flammable liquid and vapor.
In contact with water releases flammable gas.
Causes serious eye irritation.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not allow contact with water.
Handle under inert gas. Protect from moisture.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO₂, sand, extinguishing powder to extinguish.
Store in a dry place. Store in a closed container.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 2

The substance demonstrates unusual reactivity with water.

- **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 3
Reactivity = 2

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

67-64-1	acetone	25-50%
123-86-4	n-butyl acetate	25-50%
1330-20-7	xylene	2.5-10%
7429-90-5	aluminium	≤2.5%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
100-41-4	ethylbenzene	0-≤2.5%
108-88-3	toluene	0-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Extinguishing powder. Do not use water.
CO2. Do not use water.
Sand. Do not use water.
Special powder for metal fires. Do not use water.
CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

67-64-1	acetone	200 ppm
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
100-41-4	ethylbenzene	33 ppm
71-36-3	butan-1-ol	60 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
108-88-3	toluene	67 ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m ³
64-17-5	ethanol	1,800 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
7664-38-2	phosphoric acid	3 mg/m ³
67-56-1	methanol	530 ppm
67-63-0	propan-2-ol	400 ppm

- **PAC-2:**

67-64-1	acetone	3200* ppm
---------	---------	-----------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 4)

123-86-4	<i>n</i> -butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
100-41-4	ethylbenzene	1100* ppm
71-36-3	butan-1-ol	800 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
108-88-3	toluene	560 ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m ³
64-17-5	ethanol	3300* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
7664-38-2	phosphoric acid	30 mg/m ³
67-56-1	methanol	2,100 ppm
67-63-0	propan-2-ol	2000* ppm

· **PAC-3:**

67-64-1	acetone	5700* ppm
123-86-4	<i>n</i> -butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
100-41-4	ethylbenzene	1800* ppm
71-36-3	butan-1-ol	8000** ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
108-88-3	toluene	3700* ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m ³
64-17-5	ethanol	15000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
7664-38-2	phosphoric acid	150 mg/m ³
67-56-1	methanol	7200* ppm
67-63-0	propan-2-ol	12000** ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 5)

- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 6)

· **Ingredients with biological limit values:**

67-64-1 acetone

BEI 25 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 7)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Liquid
· Color:	Silver
· Odor:	Characteristic
· Odor threshold:	Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)

- **Flash point:** <-18 °C (<-0.4 °F)

- **Flammability (solid, gaseous):** Highly flammable.
Contact with water liberates extremely flammable gases.

- **Auto igniting:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

· Lower:	1.2 Vol %
· Upper:	13 Vol %

- **Vapor pressure at 20 °C (68 °F):** 233 hPa (174.8 mm Hg)

- **Vapor pressure at 50 °C (122 °F):** 800 hPa (600 mm Hg)

- **Density at 20 °C (68 °F):** 0.9097 g/cm³ (7.5914 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 8)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	80.9 %
VOC content:	≥39.96-<40.03 % 607.1 g/l / 5.07 lb/gal
· Solids content:	24.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7 xylene

3

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 9)

100-41-4	ethylbenzene	2B
108-88-3	toluene	3
112926-00-8	Precipitated silica (Silica-Amorphous)	3
64-17-5	ethanol	1
67-63-0	propan-2-ol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not hazardous for water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | <p>UN3148</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | <p>Water-reactive liquid, n.o.s. (Aluminum powder)
WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER)</p> |

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 10)

- **Transport hazard class(es)**

- **DOT**



- **Class**

4.3 Substances which, in contact with water, emit flammable gases

- **Label**

4.3

- **IMDG, IATA**



- **Class**

4.3 Substances which, in contact with water, emit flammable gases

- **Label**

4.3

- **Packing group**

- **DOT, IMDG, IATA**

II

- **Environmental hazards:**

Not applicable.

- **Special precautions for user**

Warning: Substances which, in contact with water, emit flammable gases

- **Hazard identification number (Kemler code):** 429

- **EMS Number:**

F-G,S-N

- **Segregation groups**

(SGG15) Powdered metals

- **Stowage Category**

E

- **Stowage Code**

SW2 Clear of living quarters.

- **Handling Code**

H1 Keep as dry as reasonably practicable

- **Segregation Code**

SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained.

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **Transport/Additional information:**

- **DOT**

- **Quantity limitations**

On passenger aircraft/rail: 1 L
On cargo aircraft only: 5 L

- **IMDG**

- **Limited quantities (LQ)**

500 ml

- **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 11)

· **UN "Model Regulation":** UN 3148 WATER-REACTIVE LIQUID, N.O.S. (ALUMINIUM POWDER), 4.3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

7429-90-5 aluminium

100-41-4 ethylbenzene

71-36-3 butan-1-ol

108-88-3 toluene

7664-38-2 phosphoric acid

67-56-1 methanol

67-63-0 propan-2-ol

· **TSCA (Toxic Substances Control Act):**

67-64-1 acetone

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

9004-36-8 Cellulose Acetate Butyrate

ACTIVE

1330-20-7 xylene

ACTIVE

7429-90-5 aluminium

ACTIVE

64742-48-9 Naphtha (petroleum), hydrotreated heavy

ACTIVE

64742-95-6 Solvent naphtha (petroleum), light arom.

ACTIVE

100-41-4 ethylbenzene

ACTIVE

71-36-3 butan-1-ol

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

108-88-3 toluene

ACTIVE

64-17-5 ethanol

ACTIVE

108-83-8 2,6-dimethylheptan-4-one

ACTIVE

7664-38-2 phosphoric acid

ACTIVE

67-56-1 methanol

ACTIVE

8002-74-2 Paraffin waxes and Hydrocarbon waxes

ACTIVE

67-63-0 propan-2-ol

ACTIVE

· **Hazardous Air Pollutants**

1330-20-7 xylene

100-41-4 ethylbenzene

108-88-3 toluene

67-56-1 methanol

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 12)

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

64-17-5	ethanol
---------	---------

67-56-1	methanol
---------	----------

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
---------	---------	---

1330-20-7	xylene	I
-----------	--------	---

100-41-4	ethylbenzene	D
----------	--------------	---

71-36-3	butan-1-ol	D
---------	------------	---

108-88-3	toluene	II
----------	---------	----

- **TLV (Threshold Limit Value)**

67-64-1	acetone	A4
---------	---------	----

1330-20-7	xylene	A4
-----------	--------	----

7429-90-5	aluminium	A4
-----------	-----------	----

100-41-4	ethylbenzene	A3
----------	--------------	----

108-88-3	toluene	A4
----------	---------	----

64-17-5	ethanol	A3
---------	---------	----

67-63-0	propan-2-ol	A4
---------	-------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word Danger**

- **Hazard-determining components of labeling:**

acetone

Naphtha (petroleum), hydrotreated heavy

toluene

n-butyl acetate

- **Hazard statements**

Highly flammable liquid and vapor.

In contact with water releases flammable gas.

Causes serious eye irritation.

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 13)

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, sand, extinguishing powder to extinguish.

Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 02/27/2024

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 15)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/26/2024

Trade name: 68004 SPARKLE SILVER H.O.K. B/C

(Contd. of page 14)

*HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Substances and mixtures which, in contact with water, emit flammable gases 2: Substances and mixtures which in contact with water emit flammable gases – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B**Carcinogenicity 1B: Carcinogenicity – Category 1B**Toxic to Reproduction 2: Reproductive toxicity – Category 2**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3**** Data compared to the previous version altered.**

USA